APPENDIX C CORE LOGS

APPENDIX C.1 FORMATTED CORE LOGS

October 2002

SEDIMENT CORE: WB-01 Date: 10/16/02 Time: 1415

System: Cable Vibracore Station Description: West bank of river.

Northing: 2319865.7 Easting: 2843535.9 Datum: NAD 83 Indiana West Mudline Elev. (ft): 576.2

Depth to Mudline (ft): 2.0 Penetration (ft): 11.0 Recovery (ft): 9.3 % Recovery: 85

Lab Grain Size (%)

	DESCRIPT	ION OF	SEDIMENT						
Sample No. and Sample Depth (ft)	Visual Sample Description (In-situ)*	Depth (ft)	Visual Sample Description (Compacted)	Sample No. and Sample Depth (ft)	TESTING	Gravel	Sand	Silt	Clay
FW-WB-01-CS-0-2 (0-2.4')	V. wet, (v. soft), brown to black, clayey SILT with fine to medium Sand to sandy clayey SILT with abundant petroleum sheen and odor and spots of NAPL.	1	V. wet, (v. soft), brown to black, clayey SILT with fine to medium Sand to sandy clayey SILT with abundant petroleum sheen and odor and spots of NAPL.	FW-WB-01-CS-0-2 (0-2')					
		2							
		3							
		4	Coal Tar/NAPL layer with Gravel.						
	Coal Tar/NAPL layer with Gravel.	5	Same as 0 - 3.5' below mudline.						
	Same as 0 - 4.1' below mudline.	6	Moist, (soft), brown, clayey SILT with fine Sand and scattered organic fragments throughout; organics increase with depth; shell fragments increase	FW-WB-01-CS-5-7	С				
FW-WB-01-CS-5-7	Moist, (soft), brown, clayey SILT with fine Sand and scattered organic fragments throughout; organics increase with depth; shell fragments	7	with depth.	(5-7') (MS/MSD)					
(5.9-8.3')	increase with depth.	8		FW-WB-01-CS-7- 9.3 (7-9.3')	С,В				
FW-WB-01-CS-7-		9							
9.3 (8.3-11.0')		10	BOB @ 9.3'						
		11							
	BOB @ 11.0'								
		12							
		13							

NOTES: A = Archive; B = Bioassay; C = Chemistry Analysis included PCB Aroclors, Organochlorine Pesticides, Semivolatile Organics, Metals (RCRA + Cu + Zn), oil and grease, Total Organic Carbon, and Acid Volatile Sulfides - Simultaneuosly Extracted Metals

G = Grain Size; GT = Geotechnical testing including Grain Size, Specific Gravity, Moisture Content/Bulk Density P = PCB Congeners

 $^{\star}\,$ In-situ compaction based on linear compaction ratios.

MS/MSD collected at FW-WB-01-CS-5-7



October 2002

Date: 10/16/02 Time: 1300

SEDIMENT CORE: WB-02

Station Description: Center of River.

System: Cable Vibracore

Northing: 2319857.5 Easting: 2843505.1 Datum: NAD 83 Indiana West Mudline Elev. (ft): 576.4

Depth to Mudline (ft): 1.6 Penetration (ft): 11.0 Recovery (ft): 8.9 % Recovery: 81

	DESCRIPT	ION OF	SEDIMENT		.				
Sample No. and Sample Depth (ft)	Visual Sample Description (In-situ)*	Depth (ft)	Visual Sample Description (Compacted)	Sample No. and Sample Depth (ft)	TESTING	Gravel	Sand	Silt	Clay
	V. wet, (v. soft), black, sandy SILT with Clay and petroleum sheen, odor, shell fragments and fine to medium organic debris. (ML) Not as much NAPL as WB-01 and WB-03.	1	V. wet, (v. soft), black, sandy SILT with Clay and petroleum sheen, odor, shell fragments and fine to medium organic debris. (ML) Not as much NAPL as WB-01 and WB-03.		·		•		
FW-WB-02-CS-0-				FW-WB-02-CS-0- 2.9 (0-2.9')	A				
2.9 (0-3.6')	Horizon marked by a fine shell fragmented layer.	2	Horizon marked by a fine shell fragmented layer.						
		3	Wet, (V. soft to soft), brown/olive, clayey SILT with fine Sand and scattered organics/shell fragments.						
	Wet, (V. soft to soft), brown/olive, clayey SILT with	4	Clay increases with depth.	FW-WB-02-CS-2.9-	B,C,GT				
FW-WB-02-CS-2.9- 6 (3.6-7.4')	fine Sand and scattered organics/shell fragments. Clay increases with depth.	5		6 (2.9-6')	_,-,-,-				
(5.5)		6							
		7							
		7		FW-WB-02-CS-6- 8.9 (6-8.9')	С				
		8		(0 0.0)					
FW-WB-02-CS-6- 8.9 (7.4-11')		9	DOD 0 0 0						
,		10	BOB @ 8.9'						
	BOB @ 11.0'	11							
		12							
		13							

NOTES: A = Archive; B = Bioassay; C = Chemistry Analysis included PCB Aroclors, Organochlorine Pesticides, Semivolatile Organics, Metals (RCRA + Cu + Zn), oil and grease, Total Organic Carbon, and Acid Volatile Sulfides - Simultaneuosly Extracted Metals

G = Grain Size; GT = Geotechnical testing including Grain Size, Specific Gravity, Moisture Content/Bulk Density P = PCB Congeners

* In-situ compaction based on linear compaction ratios.

CORING NOTES: Sheen observed while coring. Strong petroleum odor.



October 2002

SEDIMENT CORE: WB-02geo Date: 10/22/02

Time: 1550 System: Cable vibracore Station Description:

Northing: 2319857.5 Easting: 2843505.1 Datum: NAD 83 Indiana West Mudline Elev. (ft): 576.4

Depth to Mudline (ft): 1.5 Penetration (ft): 10.5 Recovery (ft): 9.2 % Recovery: 88

Lab Grain Size (%)

	DESCRIPTI	ON OF	SEDIMENT		"				
Sample No. and Sample Depth (ft)	Visual Sample Description (In-situ)*	Depth (ft)	Visual Sample Description (Compacted)	Sample No. and Sample Depth (ft)	TESTING	Gravel	Sand	Silt	Clav
		1							
		2							
		3	Wet, (v. soft to soft), brown to olive, clayey SILT						
WB-02 3 - 5	Wet, (v. soft to soft), brown to olive, clayey SILT with fine Sand; scattered organics; shell fragments strong petroleum odor; NAPL present.	4	with fine Sand; scattered organics; shell fragments strong petroleum odor; NAPL present.	WB-02 3 - 5 (3-5')	ии,со				
(3.4-5.7')		5	Headspace ranged from 0.01' to 0.035'.						
	Headspace ranged from 0.01' to 0.035'.								
		6	Wet, (v. soft to soft), brown to olive, clayey SILT						
	W. (7	with fine Sand; scattered organics; shell fragments clay increases with depth.	WB-02 6 - 7.6	uu,co				
	Wet, (v. soft to soft), brown to olive, clayey SILT with fine Sand; scattered organics; shell fragments clay increases with depth.		Headspace ranged from 0' to 0.009'.	(6-7.6')					
WB-02 6 - 7.6 (6-7.6')		8							
	Headspace ranged from 0' to 0.009'.								
		9	DOD 0 0 0						
		10	BOB @ 9.2'						
	BOB @ 10.5'	11							
		12							
		13							

NOTES: UU = UU Triaxial Shear Testing; CO = Consolidation Testing

Headspace measurements taken in tenths of a foot from the top of the sediment to the top of the aluminum pipe.



 $^{^{\}star}\,$ In-situ compaction based on linear compaction ratios.

October 2002

SEDIMENT CORE: WB-03

Date: 10/16/02 Time: 1205

System: Cable Vibracore

Northing: 2319863.3 Easting: 2843475.2 Datum: NAD 83 Indiana West Mudline Elev. (ft): 577.3

Depth to Mudline (ft): 0.7 Penetration (ft): 11.9 Recovery (ft): 11.2 % Recovery: 94

Station Description: West side of river.

Lab Grain Size (%)

	DESCRIPT	ION OF	SEDIMENT		g				
Sample No. and Sample Depth (ft)	Visual Sample Description (In-situ)*	Depth (ft)	Visual Sample Description (Compacted)	Sample No. and Sample Depth (ft)	TESTING	Gravel	Sand	Silt	Clay
FW-WB-03-CS-0- 1.2 (0-1.3')	V. wet, (v. soft), clayey SILT with fine Sand and organic debris and petroleum sheen and odor (high to moderate) and some NAPL.	1	V. wet, (v. soft), clayey SILT with fine Sand and organic debris and petroleum sheen and odor (high to moderate) and some NAPL.	FW-WB-03-CS-0- 1.2 (0-1.2')	A	3	.,	.,	
FW-WB-03-CS-1.2- 4 (1.3-4.2')	Wet to moist, (soft), brown, clayey SILT with fine Sand (ML). Higher organics in top 1 foot of section. (OH) Clay increasing with depth.	3	Wet to moist, (soft), brown, clayey SILT with fine Sand (ML). Higher organics in top 1 foot of section. (OH) Clay increasing with depth.	FW-WB-03-CS-1.2- 4 (1.2-4') D	C,P				
		4							
		5		FW-WB-03-CS-4-6 (4-6')	A				
FW-WB-03-CS-4-6 (4.2-6.4')		6		(+ 0)					
FW-WB-03-CS-6-		7		FW-WB-03-CS-6- 9.5 (6-9.5')	A				
9.5 (6.4-10.1')		9							
		10	Wet, (loose), tan, silty fine SAND (SM).	FW-WB-03-CS-9.5-					
FW-WB-03-CS-9.5- 11.2 (10.1-11.9')	Wet, (loose), tan, silty fine SAND (SM).	11		11.2 (9.5-11.2')	B,C,G				
()	DOD @ 44 0	12	BOB @ 11.2'						
	BOB @ 11.9'	13							

NOTES: A = Archive; B = Bioassay; C = Chemistry Analysis included PCB Aroclors, Organochlorine Pesticides, Semivolatile Organics, Metals (RCRA + Cu + Zn), oil and grease, Total Organic Carbon, and Acid Volatile Sulfides - Simultaneuosly Extracted Metals

- G = Grain Size; GT = Geotechnical testing including Grain Size, Specific Gravity, Moisture Content/Bulk Density P = PCB Congeners
- $^{\star}\,$ In-situ compaction based on linear compaction ratios.
- D = A duplicate of FW-WB-03-CS-1.2-4 was collected and designated as FW-WB-52-CS-1.2-4. It was sampled for chemistry analysis only.

CORING NOTES: Sheen observed during coring. Surface sediment appears to be crude oil.



October 2002

Date: 10/15/02 Time: 1553

System: Cable Vibracore Station Description: North side of river.

SEDIMENT CORE: WB-04

Northing: 2320627.4 Easting: 2842911.2 Datum: NAD 83 Indiana West Mudline Elev. (ft): 577.1

Depth to Mudline (ft): 0.9 Penetration (ft): 11.3 Recovery (ft): 11.3 % Recovery: 100

Lab Grain Size (%)

	DESCRIPT	ION OF	SEDIMENT	1	<u>o</u>				ı
Sample No. and Sample Depth (ft)	Visual Sample Description (In-situ)*	Depth (ft)	Visual Sample Description (Compacted)	Sample No. and Sample Depth (ft)	TESTING	Gravel	Sand	Silt	;
	V. wet, (v. soft) black, clayey SILT with fine Sand and moderate to high petroleum odor and sheen. Piece of glass at 4'. Highly contaminated. #	1	V. wet, (v. soft) black, clayey SILT with fine Sand and moderate to high petroleum odor and sheen. Piece of glass at 4'. Highly contaminated. #		•				
		2							
		3							
FW-WB-04-CS-0-8 (0-8')		4		FW-WB-04-CS-0-8 (0-8')	С				
		5							
		6							
		7							
FIN IND 04 CC 0	Maint (aft) alaumandu (fina) CU Tuith	8	Maint (asti) along and (fine) OH Torith	5W WD 04 00 0					
FW-WB-04-CS-8- 9.2 (8-9.2')	Moist, (soft), clayey sandy (fine) SILT with scattered shell fragments throughout. (ML-SM)	9	Moist, (soft), clayey sandy (fine) SILT with scattered shell fragments throughout. (ML-SM)	FW-WB-04-CS-8- 9.2 (8-9.2')	A				
FW-WB-04-CS-9.2- 11.3 (9.2-11.3')	Wet, (loose), grey to tan, fine to medium SAND with Silt. 1-2 inch layer of wood debris/sticks on surface of sand.	10	Wet, (loose), grey to tan, fine to medium SAND with Silt. 1-2 inch layer of wood debris/sticks on surface of sand.	FW-WB-04-CS-9.2- 11.3 (9.2-11.3')	С				
		11							
	BOB @ 11.3'	12	BOB @ 11.3'						
		13							

NOTES: A = Archive; B = Bioassay; C = Chemistry Analysis included PCB Aroclors, Organochlorine Pesticides, Semivolatile Organics, Metals (RCRA + Cu + Zn), oil and grease, Total Organic Carbon, and Acid Volatile Sulfides - Simultaneuosly Extracted Metals

- G = Grain Size; GT = Geotechnical testing including Grain Size, Specific Gravity, Moisture Content/Bulk Density P = PCB Congeners
- $^{\star}\,$ In-situ compaction based on linear compaction ratios.
- # Limited recovery of the upper 8 ft due to compaction or pile driving.

CORING NOTES: Tan sand in core catcher. Strong petroleum odor. Sheen created during coring.



October 2002

SEDIMENT CORE: WB-05 Date: 10/16/02

Time: 1045 System: Cable Vibracore

Northing: 2320602.6 Easting: 2842892.4 Datum: NAD 83 Indiana West Mudline Elev. (ft): 576.7

Depth to Mudline (ft): 1.2 Penetration (ft): 10.6 Recovery (ft): 10.0 % Recovery: 94

Station Description: Center of river.

	DESCRIPT	ION OF	SEDIMENT		_O				
Sample No. and Sample Depth (ft)	Visual Sample Description (In-situ)*	Depth (ft)	Visual Sample Description (Compacted)	Sample No. and Sample Depth (ft)	TESTING	Gravel	Sand	Silt	Clay
	V. wet, (loose), black (with tan layers), silty fine to medium SAND (SM) with some coarser SAND and fine Gravels and petroleum sheen and odor and scattered vegetation. Coal tar (gravel size) observed in places with NAPL associated.	1	V. wet, (loose), black (with tan layers), silty fine to medium SAND (SM) with some coarse SAND and fine Gravels and petroleum sheen and odor and scattered vegetation. Coal tar (gravel size) observed in places with NAPL associated.						
		2							
FW-WB-05-CS-2- 4.2 (2.1-4.5')		3		FW-WB-05-CS-2- 4.2 (2-4.2')	A				
		4							
	Wet to moist, (soft) black to brown, clayey SILT (OH) with fine Sand and extensive petroleum sheen and odor. Some NAPL observed	5	Wet to moist, (soft) black to brown, clayey SILT (OH) with fine Sand and extensive petroleum sheen and odor. Some NAPL observed						
FW-WB-05-CS-4.2-	throughout section. Observed hair-like fibres in sediment that may be actual hair from sewage.	6	throughout section. Observed hair-like fibres in sediment that may be actual hair from sewage.	FW-WB-05-CS-4.2- 7.5 (4.2-7.5')	C,P				
7.5 (4.5-8.0')		7		(4.2-7.3)					
	Maint (aft) have to discovered in the state of the state	8	Moist, (soft), brown to olive, clayey SILT with fine Sand and fince organics throughout depth (OH).						
	Moist, (soft), brown to olive, clayey SILT with fine Sand and fince organics throughout depth (OH).		Zone of dark material (only color change) 1-2".	FW-WB-05-CS-7.5-	B,C,G				
FW-WB-05-CS-7.5- 10 (8-10.6')	Zone of dark material (only color change) 1-2".	9		10 (7.5-10')	_,_,				
, ,		10	BOB @ 10'						
	BOB @ 10.6'	11							
		12							
		13							

NOTES: A = Archive; B = Bioassay; C = Chemistry Analysis included PCB Aroclors, Organochlorine Pesticides, Semivolatile Organics, Metals (RCRA + Cu + Zn), oil and grease, Total Organic Carbon, and Acid Volatile Sulfides - Simultaneuosly Extracted Metals

G = Grain Size; GT = Geotechnical testing including Grain Size, Specific Gravity, Moisture Content/Bulk Density P = PCB Congeners

Bottom section of core had contamination on outside. Scraped this off best we could. Some compromise of sample may occur. (material does not appear to be contaminated.)



^{*} In-situ compaction based on linear compaction ratios.

October 2002

Date: 10/15/02 Time: 1631

System: Cable vibracore

SEDIMENT CORE: WB-06

Northing: 2320565.4 Easting: 2842892.3 Datum: NAD 83 Indiana West Mudline Elev. (ft): 577.2

Depth to Mudline (ft): 0.8 Penetration (ft): 11.9 Recovery (ft): 11.9 % Recovery: 100

Station Description: South side of river.

	DESCRIPT	ION OF	SEDIMENT		_o				l
Sample No. and Sample Depth (ft)	Visual Sample Description (In-situ)*	Depth (ft)	Visual Sample Description (Compacted)	Sample No. and Sample Depth (ft)	TESTING	Gravel	Sand	Silt	Clav
	POOR RECOVERY - MOST NOT RECOVERED V. wet, (v. soft), black, clayey SILT with Sand; heavy petroleum sheen and odor.	1	POOR RECOVERY - MOST NOT RECOVERED V. wet, (v. soft), black, clayey SILT with Sand; heavy petroleum sheen and odor.						
		2							
		3							
		4							
		5							
	V wat (lease) become to grow eith, fine to godine	6	V such (loops) become to group silts fine to medium						
FW-WB-06-CS-6- 7.8	V. wet, (loose), brown to gray, silty fine to medium SAND with Clay; extensive petroleum contamination with coal tar observed.	7	V. wet, (loose), brown to gray, silty fine to medium SAND with Clay; extensive petroleum contamination with coal tar observed.	FW-WB-06-CS-6- 7.8	A				
(6-7.8')	Wet, (loose), brown to gray, fine to medium SAND lense with Silt.		Wet, (loose), brown to gray, fine to medium SAND lense with Silt.	(6-7.8')					
	Moist, (soft), brown to olive, clayey SILT with fine Sand and trace of shell fragments and fine organics throughout (OH). (Native?)#	9	Moist, (soft), brown to olive, clayey SILT with fine Sand and trace of shell fragments and fine organics throughout (OH). (Native?) #						
FW-WB-06-CS-7.8- 11.9 (7.8-11.9')		10		FW-WB-06-CS-7.8- 11.9 (7.8-11.9')	A,C				
		11							
		12							
	BOB @ 11.9'	12	BOB @ 11.9'						
		13							

NOTES: A = Archive; B = Bioassay; C = Chemistry Analysis included PCB Aroclors, Organochlorine Pesticides, Semivolatile Organics, Metals (RCRA + Cu + Zn), oil and grease, Total Organic Carbon, and Acid Volatile Sulfides - Simultaneuosly Extracted Metals

- G = Grain Size; GT = Geotechnical testing including Grain Size, Specific Gravity, Moisture Content/Bulk Density P = PCB Congeners
- $^{\star}\,$ In-situ compaction based on linear compaction ratios.
- # Concerned about "draw down" from very contaminated material above.

CORING NOTES: 7.8 - 11.9 ft may be compromised due to pore waters from above material.



October 2002

SEDIMENT CORE: WB-07b Northing: 2320632.8 Depth to Mudline (ft): 2.4 Date: 10/15/02 Easting: 28441993.4 Penetration (ft): 11.5 Recovery (ft): 9.8 Time: 1213 Datum: NAD 83 Indiana West System: Cable vibracore Mudline Elev. (ft): 575.6 % Recovery: 85

Station Description: West end of reach #1. Second core at this location.

	DESCRIPTI	ON OF	SEDIMENT		₀				
Sample No. and Sample Depth (ft)	Visual Sample Description (In-situ)*	Depth (ft)	Visual Sample Description (Compacted)	Sample No. and Sample Depth (ft)	TESTING	Gravel	Sand	Silt	Clay
FW-WB-07-CS-0-2 (0-2.3')	V. wet, (v. soft), brown, clayey SILT (OH) with trace of shell fragments (freshwater clam) to a depth of 3.5'; fragmented cattail and fragmented roots; sand increasing with depth.	1	V. wet, (v. soft), brown, clayey SILT (OH) with trace of shell fragments (freshwater clam) to a depth of 3.5'; fragmented cattail and fragmented roots; sand increasing with depth.	FW-WB-07-CS-0-2 (0-2')	A				
		2							
FW-WB-07-CS-2-4		3		FW-WB-07-CS-2-4 (2-4')	B,C,G1				
(2.3-4.7')				(= .)	P				
		4							
		5		FW-WB-07-CS-4-					
		6		7.1 (4-7.1')	A				
FW-WB-07-CS-4- 7.1 (4.7-8.3')		7							
		8	Moist to wet, (loose), tan to brown, silty fine SAND with Clay (SM). (Native)	FW-WB-07-CS-7.1-	B,C,GT				
FW-WB-07-CS-7.1-	Moist to wet, (loose), tan to brown, silty fine SAND with Clay (SM). (Native)	9	Same as above but tan, silty fine SAND lenses at approximately 8 and 9 feet (SM/SW). Each lense is approximately 2 inches.	9.4 (7.1-9.4')	B,C,G1				
9.4 (8.3-11.0')		10	Clayey SILT with Sand (Native)	FW-WB-07-CS-9.4-	Α				
	Same as above but tan, silty fine SAND lenses at approximately 8 and 9 feet (SM/SW). Each lense is approximately 2 inches.	11	BOB @ 9.8'	(9.4-9.8')					
FW-WB-07-CS-9.4- 9.8	Clayey SILT with Sand (Native)								
(11-11.5')	BOB @ 11.5'	12							
		13							

NOTES: A = Archive; B = Bioassay; C = Chemistry Analysis included PCB Aroclors, Organochlorine Pesticides, Semivolatile Organics, Metals (RCRA + Cu + Zn), oil and grease, Total Organic Carbon, and Acid Volatile Sulfides - Simultaneuosly Extracted Metals

G = Grain Size; GT = Geotechnical testing including Grain Size, Specific Gravity, Moisture Content/Bulk Density P = PCB Congeners

CORING NOTES: Lost 1.2 ft from bottom.



^{*} In-situ compaction based on linear compaction ratios.

October 2002

Date: 10/15/02 Time: 1247

SEDIMENT CORE: WB-08

Northing: 2320603.7 Easting: 2841996.2 Datum: NAD 83 Indiana West

Mudline Elev. (ft): 576.6

Depth to Mudline (ft): 1.4 Penetration (ft): 11.4 Recovery (ft): 9.9 % Recovery: 87

System: Cable vibracore

Station Description: West end of reach #7 - center core.

	DESCRIPT	ION OF	SEDIMENT	Т	<u>o</u>				l
Sample No. and Sample Depth (ft)	Visual Sample Description (In-situ)*	Depth (ft)	Visual Sample Description (Compacted)	Sample No. and Sample Depth (ft)	TESTING	Gravel	Sand	Silt	
FW-WB-08-CS-0-2 (0-2.3')	V. wet, (v. soft to soft), brown to black, clayey SILT with fine Sand and root fragments to a depth of 2' (OH). Fine sand increasing with depth.	1	V. wet, (v. soft to soft), brown to black, clayey SILT with fine Sand and root fragments to a depth of 2' (OH). Fine sand increasing with depth.	FW-WB-08-CS-0-2 (0-2')	B,C,GT				
		2							
FW-WB-08-CS-2-4		3		FW-WB-08-CS-2-4 (2-4')	A				
(2.3-4.6)		4							<u> </u>
		5							
FW-WB-08-CS-4- 7.6 (4.6-8.7)		6		FW-WB-08-CS-4- 7.6 (4-7.6')	С,СТ				
(4.0-0.7)		7							
		8	Moist, (soft), clayey sandy (fine) SILT (ML) with trace fine shell fragments.	FW-WB-08-CS-7.6-					
FW-WB-08-CS-7.6-	Moist, (soft), clayey sandy (fine) SILT (ML) with trace fine shell fragments.	9		9.9 (7.6-9.9')	A				
9.9 (8.7-11.4')		10	BOB @ 9.9'						
		11							
	BOB @ 11.4'	12							
		13							

NOTES: A = Archive; B = Bioassay; C = Chemistry Analysis included PCB Aroclors, Organochlorine Pesticides, Semivolatile Organics, Metals (RCRA + Cu + Zn), oil and grease, Total Organic Carbon, and Acid Volatile Sulfides - Simultaneuosly Extracted Metals

G = Grain Size; GT = Geotechnical testing including Grain Size, Specific Gravity, Moisture Content/Bulk Density P = PCB Congeners

CORING NOTES: Lost 0.9 ft out the bottom.



^{*} In-situ compaction based on linear compaction ratios.

October 2002

Date: 10/15/02 Time: 1419

SEDIMENT CORE: WB-09

Northing: 2320590.6 Easting: 2842016.7 Datum: NAD 83 Indiana West

Mudline Elev. (ft): 577.4

Depth to Mudline (ft): 0.6 Penetration (ft): 11.5 Recovery (ft): 10.9 % Recovery: 95

System: Cable vibracore

Station Description: End of reach #1 - south bank.

	DESCRIPT	ON OF	SEDIMENT		_o				
Sample No. and Sample Depth (ft)	Visual Sample Description (In-situ)*	Depth (ft)	Visual Sample Description (Compacted)	Sample No. and Sample Depth (ft)	TESTING	Gravel	Sand	Silt	Clay
FW-WB-09-CS-0-2	V. wet, (soft), black, clayey SILT with fine SAND and moderate petroleum odor and sheen.	1	V. wet, (soft), black, clayey SILT with fine SAND and moderate petroleum odor and sheen.	FW-WB-09-CS-0-2	A				
(0-2.1')	Wet, (soft), brown, clayey SILT with fine organics and shell fragments throughout (OH); fine sand increasing with depth; fine roots and other organics	2	Wet, (soft), brown, clayey SILT with fine organics and shell fragments throughout (OH); fine sand increasing with depth; fine roots and other organics decreasing with depth.	(0-2')					
FW-WB-09-CS-2-4	decreasing with depth.	3		FW-WB-09-CS-2-4	A				
(2.1-4.2')		,		(2-4')					
	Moist, (soft), brown, clayey SILT with fine Sand	4	Moist, (soft), brown, clayey SILT with fine Sand (ML).	FW-WB-09-CS-4-6					
FW-WB-09-CS-4-6	(ML).	5		(4-6')	С				
(4.2-6.4')		6							
FW-WB-09-CS-6-8		7		FW-WB-09-CS-6-8 (6-8')	A				
(6.4-8.5')		8							
FW-WB-09-CS-8-		9		FW-WB-09-CS-8- 10 (8-10')	С				
10 (8.5-10.6')		10	Moist, (soft to medium stiff), brown, clayey sandy	FW-WB-09-CS-10-					
FW-WB-09-CS-10- 10.9	Moist, (soft to medium stiff), brown, clayey sandy	11	SILT (ML).	10.9 (10-10.9')	Α				
(10-10.9')	SILT (ML).		BOB @ 10.9'						
	BOB @ 11.5'	12							
		13							

NOTES: A = Archive; B = Bioassay; C = Chemistry Analysis included PCB Aroclors, Organochlorine Pesticides, Semivolatile Organics, Metals (RCRA + Cu + Zn), oil and grease, Total Organic Carbon, and Acid Volatile Sulfides - Simultaneuosly Extracted Metals

G = Grain Size; GT = Geotechnical testing including Grain Size, Specific Gravity, Moisture Content/Bulk Density P = PCB Congeners

CORING NOTES: Sheen observed during coring.



^{*} In-situ compaction based on linear compaction ratios.

October 2002

SEDIMENT CORE: WB-09geo Date: 10/22/02

Time: 1235

System: Cable vibracore Station Description:

Northing: 2320590.6 Easting: 2842016.7 Datum: NAD 83 Indiana West Mudline Elev. (ft): 577.4

Depth to Mudline (ft): 0.7 Penetration (ft): 11.1 Recovery (ft): 10.3 % Recovery: 93

	DESCRIPT	ON OF	SEDIMENT		_o				ì
Sample No. and Sample Depth (ft)	Visual Sample Description (In-situ)*	Depth (ft)	Visual Sample Description (Compacted)	Sample No. and Sample Depth (ft)	TESTING	Gravel	Sand	Silt	10
		1							
		2							Ī
		3							Ì
		4	Wet, (soft), brown clayey SILT with fine to medium						
WB-09 3.8-5.5	Wet, (soft), brown clayey SILT with fine to medium Sand.	5	Sand.	WB-09 3.8-5.5 (3.8-5.5')	UU,CO				
	Wet, (soft), brown, clayey, sandy SILT with fine to medium Sand	0	Wet, (soft), brown, clayey, sandy SILT with fine to medium Sand Headspace ranged from 0.030' to 0.035'						
	Headspace ranged from 0.030' to 0.035'	6							Ì
		7							Ĭ
		8	Moist, (soft), brown clayey SILT with fine Sand.	WB-09 7.8-9.5	UU,CO				
	Moist, (soft), brown clayey SILT with fine Sand.	9	Headspace ranged from 0.0' to 0.01' above	(7.8-9.5')					
	Headspace ranged from 0.0' to 0.01' above aluminum tube.	10	aluminum tube.						
		11	BOB @ 10.3'						
	BOB @ 10.3'								Ì
		12							1
		13							

NOTES: UU = UU Triaxial Shear Testing; CO = Consoliation Testing

Headspace measurements taken in tenths of a foot from the top of the sediment to the top of the aluminum pipe.



^{*} In-situ compaction based on linear compaction ratios.

October 2002

Northing: 2319706.9

Mudline Elev. (ft): 579.3

Date: 10/17/02 Time: 1010 System: Cable vibracore

SEDIMENT CORE: WB-10

Easting: 2840998.5 Datum: NAD 83 Indiana West

Depth to Mudline (ft): 0.6 Penetration (ft): 11.4 Recovery (ft): 9.6 % Recovery: 84

Station Description: North side of river.

	DESCRIPT	ION OF	SEDIMENT		စ္				
Sample No. and Sample Depth (ft)	Visual Sample Description (In-situ)*	Depth (ft)	Visual Sample Description (Compacted)	Sample No. and Sample Depth (ft)	TESTING	Gravel	Sand	Silt	Clay
	V. wet, (v. soft) black, sandy, clayey, SILT (OH) with strong petroleum sheen and odor and fine organics (including human hair).	1	V. wet, (v. soft) black, sandy, clayey, SILT (OH) with strong petroleum sheen and odor and fine organics (including human hair).				-	·	
FW-WB-10-CS-0-				FW-WB-10-CS-0- 3.2 (0-3.2')	в,с,ст				
3.2 (0-3.8')		2		(0-3.2)	P				
		3							
		4	Wet to moist, (soft), brown to olive, clayey SILT with fine Sand and scattered fine organics and						
	Wet to moist, (soft), brown to olive, clayey SILT with fine Sand and scattered fine organics and shell fragments (OH/ML).		shell fragments (OH/ML).	FW-WB-10-CS-3.2- 6 (3.2-6')	B,C,GT				
FW-WB-10-CS-3.2- 6		5							
(3.8-7.1')		6							
		7		FW-WB-10-CS-6-8	A				
		,		(6-8')					
FW-WB-10-CS-6-8 (7.1-9.5')		8							
		9		FW-WB-10-CS-8- 9.6 (8-9.6')	A				
FW-WB-10-CS-8-		10	BOB @ 9.6'						
9.6 (9.5-11.4')		44							
		11							
	BOB @ 11.4'	12							
		13							

NOTES: A = Archive; B = Bioassay; C = Chemistry Analysis included PCB Aroclors, Organochlorine Pesticides, Semivolatile Organics, Metals (RCRA + Cu + Zn), oil and grease, Total Organic Carbon, and Acid Volatile Sulfides - Simultaneuosly Extracted Metals

G = Grain Size; GT = Geotechnical testing including Grain Size, Specific Gravity, Moisture Content/Bulk Density P = PCB Congeners



October 2002

Date: 10/17/02 Time: 1055

System: Cable vibracore Station Description: Center of river.

SEDIMENT CORE: WB-11

Northing: 2319668.9 Easting: 2841001.5 Datum: NAD 83 Indiana West Mudline Elev. (ft): 577.6

Depth to Mudline (ft): 2.3 Penetration (ft): 11.4 Recovery (ft): 9.4 % Recovery: 82

Lab Grain Size (%)

	DESCRIPT	ION OF	SEDIMENT		₍₂₎				
Sample No. and Sample Depth (ft)	Visual Sample Description (In-situ)*	Depth (ft)	Visual Sample Description (Compacted)	Sample No. and Sample Depth (ft)	TESTING	Gravel	Sand	Silt	Clay
	V. wet, (v. soft), black, organic, clayey, SILT with fine Sand (OH); moderate to heavy petroleum sheen and odor; hair-like fibers; green vegetation in top 1'; dead dragon fly (approximately 2 cm long) at 1'.	11	V. wet, (v. soft), black, organic, clayey, SILT with fine Sand (OH); moderate to heavy petroleum sheen and odor; hair-like fibers; green vegetation in top 1'; dead dragon fly (approximately 2 cm long at 1'.			3	<u>""</u>	<u> </u>	
FW-WB-11-CS-0-4		2		FW-WB-11-CS-0-4 (0-4')	С				
(0-4.8')		3		(6.1)					
		3							
		4	Wet, (soft), olive to brown, clayey SILT with fine						
		5	Sand and fine organics; scattered shell fragments. (Native?)	FW-WB-11-CS-4-6	С				
FW-WB-11-CS-4-6	Wet, (soft), olive to brown, clayey SILT with fine Sand and fine organics; scattered shell fragments. (Native?)			(4-6)					
(4.8-7.3')		6							
		7		FW-WB-11-CS-6-8 (6-8)	A				
		8		, ,					
FW-WB-11-CS-6-8									
(7.3-9.7')		9	Scattered vegetation and wood chips at base of core.	FW-WB-11-CS-8- 9.4 (8-9.4')	A				
		10	BOB @ 9.4'						
FW-WB-11-CS-8- 9.4									
(9.7-11.4')	Scattered vegetation and wood chips at base of core.	11							
	BOB @ 11.4'	12							
		13							Ш_

NOTES: A = Archive; B = Bioassay; C = Chemistry Analysis included PCB Aroclors, Organochlorine Pesticides, Semivolatile Organics, Metals (RCRA + Cu + Zn), oil and grease, Total Organic Carbon, and Acid Volatile Sulfides - Simultaneuosly Extracted Metals

G = Grain Size; GT = Geotechnical testing including Grain Size, Specific Gravity, Moisture Content/Bulk Density P = PCB Congeners

CORING NOTES: Coring created a petroleum sheen on the water surface.



^{*} In-situ compaction based on linear compaction ratios.

October 2002

Date: 10/17/02 Time: 1120 System: Cable vibracore

SEDIMENT CORE: WB-12

Northing: 2319628.9 Easting: 2841004.3 Datum: NAD 83 Indiana West Mudline Elev. (ft): 578.8

Depth to Mudline (ft): 1.1 Penetration (ft): 10.9 Recovery (ft): 9..4 % Recovery: 86

Station Description: South side of river.

	DESCRIPT	ION OF	SEDIMENT	_					
Sample No. and Sample Depth (ft)	Visual Sample Description (In-situ)*	Depth (ft)	Visual Sample Description (Compacted)	Sample No. and Sample Depth (ft)	TESTING	Gravel	Sand	Silt	Clay
	V. wet, (v. soft), black, clayey SILT with fine Sand and organics throughout (including human hair); moderate/extensive petroleum sheen/NAPL and odor.	1	V. wet, (v. soft), black, clayey SILT with fine Sand and organics throughout (including human hair); moderate/extensive petroleum sheen/NAPL and odor.						
FW-WB-12-CS-0-4		2		FW-WB-12-CS-0-4 (0-4')	A				
(0-4.6')		3							
		4	Wet, (soft), tan to brown, clayey SILT with Sand						
	Wet, (soft), tan to brown, clayey SILT with Sand	5	(ML) alternating with wet, (loose), tan, silty fine to medium SAND (SM). (Native)	FW-WB-12-CS-4-6 (4-6')	С				
FW-WB-12-CS-4-6 (4.6-7')	(ML) alternating with wet, (loose), tan, silty fine to medium SAND (SM). (Native)	6							
(4.0-7)		7	1-2 inch shell fragment layers at 7 ft.	FW-WB-12-CS-6- 8.5 (6-8.5')	в,с				
FW-WB-12-CS-6-	1-2 inch shell fragment layers at 7 ft.	8							
8.5 (7-9.9')		9	Wet, (loose), tan, fine to medium SAND (SW). (Native)	FW-WB-12-CS-8.5- 9.4 (8.5-9.4')	A				
FW-WB-12-CS-8.5-	Wet, (loose), tan, fine to medium SAND (SW).	10	BOB @ 9.4'						
9.4 (9.9-10.9')	(Native) BOB @ 10.9	11							
	e.vi @ aoa	12							
1		13							

NOTES: A = Archive; B = Bioassay; C = Chemistry Analysis included PCB Aroclors, Organochlorine Pesticides, Semivolatile Organics, Metals (RCRA + Cu + Zn), oil and grease, Total Organic Carbon, and Acid Volatile Sulfides - Simultaneuosly Extracted Metals

G = Grain Size; GT = Geotechnical testing including Grain Size, Specific Gravity, Moisture Content/Bulk Density P = PCB Congeners

* In-situ compaction based on linear compaction ratios.

CORING NOTES: Refusal encountered at 10.9 ft.

Petroleum sheen created from coring.



October 2002

Northing: 2319636.3 Easting: 2840999.5 SEDIMENT CORE: WB-12geo Date: 10/22/02 Time: 1015 Datum: NAD 83 Indiana West System: Cable vibracore Mudline Elev. (ft): 578.8

Depth to Mudline (ft): 1.5 Penetration (ft): 10.4 Recovery (ft): 8.6 % Recovery: 83

Station Description: Geotechnical core - south side of river.

Lab Grain Size (%)

	DESCRIPT	ION OF	SEDIMENT		ဗ				l
Sample No. and Sample Depth (ft)	Visual Sample Description (In-situ)*	Depth (ft)	Visual Sample Description (Compacted)	Sample No. and Sample Depth (ft)	TESTING	Gravel	Sand	Silt	:
		1							
		2							
		3							
		4	Wet, (loose), dark brown to black, silty SAND with trace organics; slight petroleum odor.	WB-12 3.5-5 (3.5-5')	UU,CO				
WB-12 3.5-5	Wet, (loose), dark brown to black, silty SAND with trace organics; slight petroleum odor.	5							
(4.2-6.1')		6	Wet, (soft), dark brow,n clayey, sandy SILT with organics (peat).	WB-12 5-6.5 (5-6.5')	UU,CO				
WB-12 5-6.5 (6.1-7.9')	Wet, (soft), dark brown, clayey, sandy SILT with organics (peat).	7	Wet, (loose), brown, silty SAND (at top).	WB-12 6.5-7.8 (6.5-7.8')	DS				
		8	Wet, (loose), tan, fine to medium SAND (at base).						
WB-12 6.5-7.8	Wet, (loose), brown, silty SAND (at top).								
(7.9-9.4')	Wet, (loose), tan, fine to medium SAND (at base).	9	BOB @ 8.6'						
		10							
	BOB @ 10.4'	11							J
		12							
		13							

NOTES: UU = UU Triaxial Shear testing; CO = Consolidation Testing; DS = Direct Shear Testing.



^{*} In-situ compaction based on linear compaction ratios.

October 2002

Date: 10/17/02 Time: 1230

System: Cable vibracore Station Description:

SEDIMENT CORE: WB-13

Northing: 2319901.1 Easting: 2839937.2 Datum: NAD 83 Indiana West Mudline Elev. (ft): 579.2

Depth to Mudline (ft): 0.7 Penetration (ft): 11.4 Recovery (ft): 9.6 % Recovery: 84

	DESCRIPT	ION OF	SEDIMENT	T	<u>o</u>				i i
Sample No. and Sample Depth (ft)	Visual Sample Description (In-situ)*	Depth (ft)	Visual Sample Description (Compacted)	Sample No. and Sample Depth (ft)	TESTING	Gravel	Sand	Silt	Clav
FW-WB-13-CS-0- 2.1 (0-2.5)	Wet, (v. soft), black, clayey SILT with fine Sand; strong petroleum odor and abundant sheen.	1	Wet, (v. soft), black, clayey SILT with fine Sand; strong petroleum odor and abundant sheen.	FW-WB-13-CS-0- 2.1 (0-2.1')	A				
(0-2.5)		2							
FW-WB-13-CS-2.1- 4 (2.5-4.8')	Clay increases with depth; NAPL globules observed throughout.	3	Clay increases with depth; NAPL globules observed throughout.	FW-WB-13-CS-2.1- 4 (2.1-4')	A				
		5		FW-WB-13-CS-4- 6.1 (4-6.1')	C,GT				
FW-WB-13-CS-4- 6.1		6							ı
(4.8-7.3')		7	Petroleum sheen ends. Wet to moist, (soft), olive brown, clayey SILT with fine Sand (ML); scattered shell fragments. (Native?)						
	Petroleum sheen ends. Wet to moist, (soft), olive brown, clayey SILT with fine Sand (ML); scattered shell fragments. (Native?)	8		FW-WB-13-CS-6.1- 9.6 (6.1-9.6') D	B,C,GT				
FW-WB-13-CS-6.1- 9.6	(Nauve:)	9							İ
(7.3-11.4')		10	BOB @ 9.6'						
		11							1
	BOB @ 11.4'	12							İ
		13							Ī

NOTES: A = Archive; B = Bioassay; C = Chemistry Analysis included PCB Aroclors, Organochlorine Pesticides, Semivolatile Organics, Metals (RCRA + Cu + Zn), oil and grease, Total Organic Carbon, and Acid Volatile Sulfides - Simultaneuosly Extracted Metals

- G = Grain Size; GT = Geotechnical testing including Grain Size, Specific Gravity, Moisture Content/Bulk Density P = PCB Congeners
- $^{\star}\,$ In-situ compaction based on linear compaction ratios.
- D = A duplicate was collected for FW-WB-13-CS-6.1-9.6 and designated FW-WB-60-CS-6.1-9.6. It was analyzed for Geotech only.



October 2002

SEDIMENT CORE: WB-14

Date: 10/17/02 Time: 1320

System: Cable vibracore Station Description:

Northing: 2319862.97 Easting: 2839916.1 Datum: NAD 83 Indiana West Mudline Elev. (ft): 578.3

Depth to Mudline (ft): 1.6 Penetration (ft): 11.5 Recovery (ft): 9.7 % Recovery: 84

	DESCRIPT	ON OF	SEDIMENT	1	စ္				ı
Sample No. and Sample Depth (ft)	Visual Sample Description (In-situ)*	Depth (ft)	Visual Sample Description (Compacted)	Sample No. and Sample Depth (ft)	TESTING	Gravel	Sand	Silt	7.0
FW-WB-14-CS-0-2 (0-2.4')	V. wet, (v. soft), black, clayey SILT with SAND and extensive petroleum contamination.	1	V. wet, (v. soft), black, clayey SILT with SAND and extensive petroleum contamination.	514 14 00 0 0	B,C				
FW-WB-14-CS-2- 3.8 (2.4-4.6')		3		FW-WB-14-CS-2- 3.8 (2-3.8')	A				
FW-WB-14-CS-3.8-	Texture change, v. soft to soft.	5	Texture change, v. soft to soft.	FW-WB-14-CS-3.8- 6.2 (3.8-6.2')	A				
6.2 (4.6-7.4')		7	Petroleum sheen ends. Wet to moist, (soft), olive brown, clayey SILT with fine SAND and scattered shell fragments and fine organics (ML). (Native?)						
FW-WB-14-CS-6.2- 9.7 (7.4-11.5')	Petroleum sheen ends. Wet to moist, (soft), olive brown, clayey SILT with fine SAND and scattered shell fragments and fine organics (ML). (Native?)	8		FW-WB-14-CS-6.2- 9.7 (6.2-9.7')	С				
		10	BOB @ 9.7'						
	BOB @ 11.5'	11							
		12							

NOTES: A = Archive; B = Bioassay; C = Chemistry Analysis included PCB Aroclors, Organochlorine Pesticides, Semivolatile Organics, Metals (RCRA + Cu + Zn), oil and grease, Total Organic Carbon, and Acid Volatile Sulfides - Simultaneuosly Extracted Metals

G = Grain Size; GT = Geotechnical testing including Grain Size, Specific Gravity, Moisture Content/Bulk Density P = PCB Congeners



October 2002

SEDIMENT CORE: WB-15

Date: 10/17/02 Time: 1200

System: Cable vibracore Station Description:

Northing: 2839890.2 Easting: 2319824.4 Datum: NAD 83 Indiana West Mudline Elev. (ft): 579.2

Depth to Mudline (ft): 0.7 Penetration (ft): 11.4 Recovery (ft): 9.4 % Recovery: 82

Lab Grain Size (%)

	DESCRIPT	ION OF	SEDIMENT		_O				ı
Sample No. and Sample Depth (ft)	Visual Sample Description (In-situ)*	Depth (ft)	Visual Sample Description (Compacted)	Sample No. and Sample Depth (ft)	TESTING	Gravel	Sand	Silt	Clav
FW-WB-15-CS-0- 0.9 (0-1.1')	V. wet, (v. soft), black, clayey SILT with fine Sand and moderate petroleum sheen and odor.	1	V. wet, (v. soft), black, clayey SILT with fine Sand and moderate petroleum sheen and odor.	FW-WB-15-CS-0- 0.9 (0-0.9')	A				
	V. wet to wet to moist, (soft), olive brown, clayey SILT with fine Sand and scattered shell fragments and fine organics (ML).	2	V. wet to wet to moist, (soft), olive brown, clayey SILT with fine Sand and scattered shell fragments and fine organics (ML).	FW-WB-15-CS-0.9- 3 (0.9-3')	C,P				
FW-WB-15-CS-3-5	Shell lense.	4	Shell lense.	FW-WB-15-CS-3-5 (3-5')	С				
(3.6-6.0')		5		FW-WB-15-CS-5-7	_				
FW-WB-15-CS-5-7		7	Shell lense.	(5-7')	A				
(6.0-8.4')	Shell lense.	8		FW-WB-15-CS-7- 9.4 (7-9.4')	A				
		9		(, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1,					
FW-WB-15-CS-7- 9.4 (8.4-11.4')		10	BOB @ 9.4'						
		11							
	BOB @ 11.4'	12							
		13							

NOTES: A = Archive; B = Bioassay; C = Chemistry Analysis included PCB Aroclors, Organochlorine Pesticides, Semivolatile Organics, Metals (RCRA + Cu + Zn), oil and grease, Total Organic Carbon, and Acid Volatile Sulfides - Simultaneuosly Extracted Metals

G = Grain Size; GT = Geotechnical testing including Grain Size, Specific Gravity, Moisture Content/Bulk Density P = PCB Congeners

CORING NOTES: Coring created a petroleum sheen.



^{*} In-situ compaction based on linear compaction ratios.

October 2002

SEDIMENT CORE: WB-16 Date: 10/18/02

Time: 0958 System: Cable vibracore Northing: 2320828.25 Easting: 2838305.11 Datum: NAD 83 Indiana West Mudline Elev. (ft):

Depth to Mudline (ft): 0.0 Penetration (ft): 10.7 Recovery (ft): 8.0 % Recovery: 75

Station Description: Edge of marsh - north side of river.

	DESCRIPT	ON OF	SEDIMENT		_O				
Sample No. and Sample Depth (ft)	Visual Sample Description (In-situ)*	Depth (ft)	Visual Sample Description (Compacted)	Sample No. and Sample Depth (ft)	TESTING	Gravel	Sand	Silt	Clay
FW-WB-16-CS-0- 1.9 (0-2.5')	V. wet, (v. loose), black, silty fine to medium SANL with extensive petroleum sheen and odor; misc organics.	1	V. wet, (v. loose), black, silty fine to medium SAND with extensive petroleum sheen and odor; misc organics.	FW-WB-16-CS-0- 1.9 (0-1.9')	A				
FW-WB-16-CS-1.9- 5.2	V. wet, (v. soft), black, clayey, sandy SILT with extensive petroleum sheen and odor; misc organics; NAPL globules with coal tar type materia (gravels).	3 4	V. wet, (v. soft), black, clayey, sandy SILT with extensive petroleum sheen and odor; misc organics; NAPL globules with coal tar type materia (gravels).	FW-WB-16-CS-1.9- 5.2 (1.9-5.2') D	B,C,GT,				
(2.5-6.8')		5	End of visible petroleum. Wet to moist, (soft), olive brown, clayey SILT with fine Sand (ML/OH); Peaty; extensive shell fragments/fine organics (Native).	FW-WB-16-CS-5.2- 8.0 (5.2-8')	С				
	End of visible petroleum. Wet to moist, (soft), olive brown, clayey SILT with fine Sand (ML/OH); Peaty; extensive shell fragments/fine organics (Native).	7		(0.2-0)					
FW-WB-16-CS-5.2- 8.0 (6.8-10.7')		9	BOB @ 8.0'						
		10							
	BOB @ 10.7'	11							
		13							

NOTES: A = Archive; B = Bioassay; C = Chemistry Analysis included PCB Aroclors, Organochlorine Pesticides, Semivolatile Organics, Metals (RCRA + Cu + Zn), oil and grease, Total Organic Carbon, and Acid Volatile Sulfides - Simultaneuosly Extracted Metals

G = Grain Size; GT = Geotechnical testing including Grain Size, Specific Gravity, Moisture Content/Bulk Density P = PCB Congeners

D = A duplicate was collected for FW-WB-16-CS-1.9-5.2 and designated FW-WB-70-CS-1.9-5.2. It was analyzed for PCB Congeners only.



 $^{^{\}star}\,$ In-situ compaction based on linear compaction ratios.

October 2002

Date: 10/18/02 Time: 1125

System: Cable Vibracore Station Description: Middle of river.

SEDIMENT CORE: WB-17

Northing: 2320801.45 Easting: 2838317.62 Datum: NAD 83 Indiana West Mudline Elev. (ft): 579.2

Depth to Mudline (ft): 0.4 Penetration (ft): 10.4 Recovery (ft): 8.3 % Recovery: 80

	DESCRIPT	ION OF	SEDIMENT	T	_o				
Sample No. and Sample Depth (ft)	Visual Sample Description (In-situ)*	Depth (ft)	Visual Sample Description (Compacted)	Sample No. and Sample Depth (ft)	TESTING	Gravel	Sand	Silt	Clav
	V. wet, (v. loose to loose), black, silty fine to medium SAND with abundant organics; petroleum sheen and odor; misc. organics throughout. 2-3 large gravels in top 1 ft.	1	V. wet, (v. loose to loose), black, silty fine to medium SAND with abundant organics; petroleum sheen and odor; misc. organics throughout. 2-3 large gravels in top 1 ft.						
FW-WB-17-CS-0- 3.8	2 o large gravele in top 1 it.	2	2 o digo gravolo in top i it.	FW-WB-17-CS-0- 3.8 (0-3.8')	B,C,G	1	91	8	1
(0-4.8')		3							
		4	Wet, (v. soft to soft), black, clayey, sandy SILT with	FW-WR-17-CS-3 8-					
		. 5	abundant organiccs, petroleum sheen and odor.	5.6 (3.8-5.6')	A				
FW-WB-17-CS-3.8-	Wet, (v. soft to soft), black, clayey, sandy SILT with abundant organics, petroleum sheen and odor.								
5.6 (4.8-7')		6	Wet to moist, (soft), olive brown, clayey SILT with fine Sand and trace shell fragments (ML/OH); organics increase with depth; shell fragments	FW-WB-17-CS-5.6-	С				
	Wet to moist, (soft), olive brown, clayey SILT with fine Sand and trace shell fragments (ML/OH);	7	increase at bottom. (Native?)	8.3 (5.6-8.3')					
FW-WB-17-CS-5.6- 8.3	organics increase with depth; shell fragments increase at bottom. (Native?)	8	Peat Zone. Same as 5.6 - 7.3 ft bgs.						
(7-10.4')		9	BOB @ 8.3'						
	Peat Zone.	10							
	Same as 7 - 9.1 ft bgs.	1							
	BOB @ 10.4	11							
		12							
		13							

NOTES: A = Archive; B = Bioassay; C = Chemistry Analysis included PCB Aroclors, Organochlorine Pesticides, Semivolatile Organics, Metals (RCRA + Cu + Zn), oil and grease, Total Organic Carbon, and Acid Volatile Sulfides - Simultaneuosly Extracted Metals

G = Grain Size; GT = Geotechnical testing including Grain Size, Specific Gravity, Moisture Content/Bulk Density P = PCB Congeners



October 2002

SEDIMENT CORE: WB-18 Northing: 2320776.28 Date: 10/18/02 Easting: 2838311.74 Time: 1155 Datum: NAD 83 Indiana West System: Cable vibracore Mudline Elev. (ft): 579.3

Depth to Mudline (ft): 0.3 Penetration (ft): 10.8 Recovery (ft): 9.3 % Recovery: 86

Station Description: Very shallow water - south side of river.

	DESCRIPT	ON OF	SEDIMENT	1	<u>ల</u>				
Sample No. and Sample Depth (ft)	Visual Sample Description (In-situ)*	Depth (ft)	Visual Sample Description (Compacted)	Sample No. and Sample Depth (ft)	TESTING	Gravel	Sand	Silt	Clav
FW-WB-18-CS-0- 3.7 (0-4.3')	V. wet, (v. loose), black, silty, fine to medium SAND with abundant misc. organics; petroleum sheen and odor; woody debris on surface; sewage related materials.	1 2	V. wet, (v. loose), black, silty, fine to medium SAND with abundant misc. organics; petroleum sheen and odor; woody debris on surface; sewage related materials.	FW-WB-18-CS-0- 3.7 (0-3.7')	A				
		3	V. wet to wet, (soft), black, clayey SILT with fine Sand; abundant misc. organics (OH).						
	V. wet to wet, (soft), black, clayey SILT with fine Sand; abundant misc. organics (OH).	5	Tan/brown sand lense (1-2 inches).	FW-WB-18-CS-3.7- 6.5 (3.7-6.5')	С				
FW-WB-18-CS-3.7- 6.5 (4.3-7.5')	Tan/brown sand lense (1-2 inches).	6	Same as 3.7 - 5.1 ft below mudline. Peat layer towards bottom of interval.						
	Same as 4.3 - 5.9 ft below mudline. Peat layer towards bottom of interval.	7	Wet to moist, (loose), tan, fine to medium SAND with trace Silt and scattered shell fragments. (Native)						
	Wet to moist, (loose), tan, fine to medium SAND with trace Silt and scattered shell fragments. (Native)	8		FW-WB-18-CS-6.5- 9.3 (6.5-9.3')	B,C,G				
FW-WB-18-CS-6.5- 9.3 (7.5-10.8')		9							
		10	BOB @ 9.3'						
	BOB @ 10.8'	11							
		13							

NOTES: A = Archive; B = Bioassay; C = Chemistry Analysis included PCB Aroclors, Organochlorine Pesticides, Semivolatile Organics, Metals (RCRA + Cu + Zn), oil and grease, Total Organic Carbon, and Acid Volatile Sulfides - Simultaneuosly Extracted Metals

G = Grain Size; GT = Geotechnical testing including Grain Size, Specific Gravity, Moisture Content/Bulk Density P = PCB Congeners

 $^{\star}\,$ In-situ compaction based on linear compaction ratios.

Sand in base of core; compaction likely occurred in upper core, therefore, recovers core length used in evaluation.



October 2002

Date: 10/21/02 Time: 1630

SEDIMENT CORE: WB-18geo

System: Cable vibracore Station Description:

Northing: 2320776.28 Easting: 2838311.74 Datum: NAD 83 Indiana West Mudline Elev. (ft): 579.3

Depth to Mudline (ft): NA Penetration (ft): 10.8 Recovery (ft): 9.8 % Recovery: 91

	DESCRIPTI	ION OF	SEDIMENT		.,				
Sample No. and Sample Depth (ft)	Visual Sample Description (In-situ)*	Depth (ft)	Visual Sample Description (Compacted)	Sample No. and Sample Depth (ft)	TESTING	Gravel	Sand	Silt	Clay
		1							
		2							
		3							
		4							
WB-18 4.5-6 (4.9-6.6')	V. wet, (soft), dark brown to black, clayey SILT with fine Sand; abundant organics; trace shell fragments.	5	V. wet, (soft), dark brown to black, clayey SILT with fine Sand; abundant organics; trace shell fragments.	WB-18 4.5-6 (4.5-6')	ии,со				
	Wet, loose, brown SILT and SAND. Headspace ranged from 0.02' to 0.015'.	7	Wet, loose, brown SILT and SAND. Headspace ranged from 0.02' to 0.015'.						
		8	Wet, (loose), same as above Wet to moist, (loose), tan, fine to medium SAND	WB-18 7.5-9 (7.5-9')	DS				
WB-18 7.5-9 (8.3-9.9')	Wet, (loose), same as above	9	with trace Silt; abundant shell frags. (Native) (Native)						
(6.6 6.6)	Wet to moist, (loose), tan, fine to medium SAND with trace Silt; abundant shell frags. (Native)	10							
		11	BOB @ 9.8'						
	BOB @ 10.8'								
		12							
		13							

NOTES: DS = Direct Shear Testing; UU = UU Triaxial Shear Testing; CO = Consolidation Testing.

Headspace measurements taken in tenths of a foot from the top of the sediment to the top of the aluminum pipe.



^{*} In-situ compaction based on linear compaction ratios.

October 2002

SEDIMENT CORE: WB-19 Date: 10/18/02

Time: 1430 System: Cable vibracore

Northing: 2320927.9 Easting: 2837530.4 Datum: NAD 83 Indiana West Mudline Elev. (ft): 579.0

Depth to Mudline (ft): 0.6 Penetration (ft): 11.0 Recovery (ft): 8.8 % Recovery: 80

Station Description: North side of river.

	DESCRIPT	ION OF	SEDIMENT	1	<u>9</u>				1
Sample No. and Sample Depth (ft)	Visual Sample Description (In-situ)*	Depth (ft)	Visual Sample Description (Compacted)	Sample No. and Sample Depth (ft)	TESTING	Gravel	Sand	Silt	Clay
FW-WB-19-CS-0-2	V. wet, (v. soft), black, clayey, sandy SILT with organic debris; slight petroleum sheen and odor; large piece of glass.	1	V. wet, (v. soft), black, clayey, sandy SILT with organic debris; slight petroleum sheen and odor; large piece of glass.	FW-WB-19-CS-0-2 (0-2')	в,с				
				(02)					1
(0-2.5')		2	Wet to moist, (v. soft to soft), olive brown, clayey SILT with fine Sand and fine organics throughout sample; trace shell fragments (ML). (Native?)						
FINAND 40 00 0 4	Wet to moist, (v. soft to soft), olive brown, clayey SILT with fine Sand and fine organics throughout	3		FW-WB-19-CS-2-4	С				Ì
FW-WB-19-CS-2-4 (2.5-5')	sample; trace shell fragments (ML). (Native?)	4		(2-4')					ı
		4							
		5		FW-WB-19-CS-4-6	A				
				(4-6')					Ì
FW-WB-19-CS-4-6		6							
(5-7.5')		7							
				FW-WB-19-CS-6- 8.8 (6-8.8')	A				
		8							
FW-WB-19-CS-6- 8.8		9							
(7.5-11')			BOB @ 8.8'						ì
		10]
		11							
	BOB @ 11.0'	10							Ì
		12							1
		13							1

NOTES: A = Archive; B = Bioassay; C = Chemistry Analysis included PCB Aroclors, Organochlorine Pesticides, Semivolatile Organics, Metals (RCRA + Cu + Zn), oil and grease, Total Organic Carbon, and Acid Volatile Sulfides - Simultaneuosly Extracted Metals

G = Grain Size; GT = Geotechnical testing including Grain Size, Specific Gravity, Moisture Content/Bulk Density P = PCB Congeners



October 2002

Date: 11/18/02 Time: 1501

System: Cable vibracore Station Description:

SEDIMENT CORE: WB-20

Northing: 2320893.3 Easting: 2837521.9 Datum: NAD 83 Indiana West Mudline Elev. (ft): 579.0

Depth to Mudline (ft): 0.7 Penetration (ft): 10.8 Recovery (ft): 8.8 % Recovery: 81

	DESCRIPT	ION OF	SEDIMENT	1	<u>o</u>				l
Sample No. and Sample Depth (ft)	Visual Sample Description (In-situ)*	Depth (ft)	Visual Sample Description (Compacted)	Sample No. and Sample Depth (ft)	TESTING	Gravel	Sand	Silt	yel C
	Wet, (loose), black, clayey, silty SAND (SM) with abundant organics throughout; slight to moderate sheen.	1	Wet, (loose), black, clayey, silty SAND (SM) with abundant organics throughout; slight to moderate sheen.						
FW-WB-20-CS-0- 2.8 (0-3.4')				FW-WB-20-CS-0- 2.8 (0-2.8')	A				
		2							
		3	Wet, (loose), black, clayey, sandy SILT (ML);						
	Wet, (loose), black, clayey, sandy SILT (ML); strong petroleum odor at base of interval.	4	strong petroleum odor at base of interval.	FW-WB-20-CS-2.8- 5.5 (2.8-5.5')	С,GT				
FW-WB-20-CS-2.8- 5.5 (3.4-6.8')		5							
		6	Wet, (v. soft to soft), brown to olive brown clayey SILT with fine Sand and organics (ML/OH).						
	Wet, (v. soft to soft), brown to olive brown clayey	7	Peat at 6.2 and 6.8 ft below mudline.	FW-WB-20-CS-5.5- 8.8 (5.5-8.8')	в,с				
	SILT with fine Sand and organics (ML/OH).	8							
	Peat at 7.6 and 8.4 ft below mudline.								
FW-WB-20-CS-5.5- 8.8 (6.8-10.8')		9	BOB @ 8.8'						
(0.0 10.0)		40	DOD @ 0.0						
		10							
	BOB @ 10.8'	11							
	10.0 W 10.0	40							
		12							
		13							}

NOTES: A = Archive; B = Bioassay; C = Chemistry Analysis included PCB Aroclors, Organochlorine Pesticides, Semivolatile Organics, Metals (RCRA + Cu + Zn), oil and grease, Total Organic Carbon, and Acid Volatile Sulfides - Simultaneuosly Extracted Metals

G = Grain Size; GT = Geotechnical testing including Grain Size, Specific Gravity, Moisture Content/Bulk Density P = PCB Congeners



October 2002 Northing: 2320852.93

Easting: 2837512.13

Date: 10/18/02 Time: 1545

SEDIMENT CORE: WB-21

Datum: NAD 83 Indiana West System: Cable vibracore Mudline Elev. (ft): 578.9 Station Description: South side of river.

Depth to Mudline (ft): 0.8 Penetration (ft): 11 Recovery (ft): 8.7 % Recovery: 79

	DESCRIPT	ION OF	SEDIMENT		g				
Sample No. and Sample Depth (ft)	Visual Sample Description (In-situ)*	Depth (ft)	Visual Sample Description (Compacted)	Sample No. and Sample Depth (ft)	TESTING	Gravel	Sand	Silt	Clay
	V. wet, (v. soft), black clayey, sandy (fine to medium) SILT with moderate petroleum sheen and odor; misc. organics throughout.		V. wet, (v. soft), black clayey, sandy (fine to medium) SILT with moderate petroleum sheen and odor; misc. organics throughout.						
		1		FW-WB-21-CS-0- 3.5	C,G,P				
		2		(0-3.5') (MS/MSD)					
FW-WB-21-CS-0- 3.5			Peat observed; organics increased at 2-3 ft below mudline.						
(0-4.7')		3							
			V. wet to wet, (v. soft to soft), brown to olive brown clayey SILT with fine sand and organics (ML/OH); organics increase with depth.						
		4		FW-WB-21-CS-3.5-	B,C,G				
		5	Tan sand lense at 4.6 ft below mudline.	(3.5-6')					
	V. wet to wet, (v. soft to soft), brown to olive brown, clayey SILT with fine sand and organics		Tan sand lense at 5.0 ft below mudline.						
	(ML/OH); organics increase with depth.	6	Shell hash at 5 - 6 ft below mudline.						
FW-WB-21-CS-3.5- 6	Tan sand lense at 6.2 ft below mudline.								
(4.7-8')	Tan sand lense at 6.7 ft below mudline.	7		FW-WB-21-CS-6- 8.2	Α				
	Shell hash at 6.7 - 8 ft below mudline.			(6-8.2')					
		8	Peat/wood at bottom of core (PT).						
		9	BOB @ 8.2'						
FW-WB-21-CS-6- 8.2									
(8-11')		10							
	Peat/wood at bottom of core (PT).	11							
	BOB @ 11.0'								
		12							
		13							

NOTES: A = Archive; B = Bioassay; C = Chemistry Analysis included PCB Aroclors, Organochlorine Pesticides, Semivolatile Organics, Metals (RCRA + Cu + Zn), oil and grease, Total Organic Carbon, and Acid Volatile Sulfides - Simultaneuosly Extracted Metals

G = Grain Size; GT = Geotechnical testing including Grain Size, Specific Gravity, Moisture Content/Bulk Density P = PCB Congeners

 $^{\star}\,$ In-situ compaction based on linear compaction ratios.

MS/MSD collected at FW-WB-21-CS-0-3.5 and analyzed for PCB Congeners.



October 2002

SEDIMENT CORE: WB-22 Date: 10/19/02

Time: 1404 System: Cable vibracore Station Description:

Northing: 2321153.41 Easting: 2836764.6 Datum: NAD 83 Indiana West Mudline Elev. (ft): 578.5

Depth to Mudline (ft): 1.2 Penetration (ft): 10.9 Recovery (ft): 8.5 % Recovery: 78

Lab Grain Size (%)

	DESCRIPT	ION OF	ON OF SEDIMENT						
Sample No. and Sample Depth (ft)	Visual Sample Description (In-situ)*	Depth (ft)	Visual Sample Description (Compacted)	Sample No. and Sample Depth (ft)	TESTING	Gravel	Sand	Silt	Clav
FW-WB-22-CS-0- 1.9 (0-2.4')	V. wet, (v. soft), black, clayey, sandy SILT with abundant misc. organics; slight petroleum sheen and moderate petroleum odor.	1	V. wet, (v. soft), black, clayey, sandy SILT with abundant misc. organics; slight petroleum sheen and moderate petroleum odor.	FW-WB-22-CS-0- 1.9 (0-1.9')	A		,		_
	Consisitencey change. Sand decreases and Clay		Consisitencey change. Sand decreases and Clay increases. Still have petroleum sheen and odor.	FW-WB-22-CS-1.9- 3.6 (1.9-3.6')	A				
SILT with fine Sand and scattered shell fragment	increases. Still have petroleum sheen and odor.	3							
	4	Wet to moist, (soft), brown to olive brown, clayey SILT with fine Sand and scattered shell fragments (towards bottom); organic material (Peat) towards	FW-WB-22-CS-3.6-	B,C,G					
		6	bottom (ML/OH).	6 (3.6-6')	В,С,С				
(4.6-7.7')		7		FW-WB-22-CS-6- 8.2 (6-8.2') D (MS/MSD)	C,G				
		8							Ī
FW-WB-22-CS-6- 8.2 (7.7-10.5')		9	Wet, (loose), tan, F-M SAND with Silt and scatterd to moderate shell fragments. (Native) BOB @ 8.5'						
(,		10	505 @ 0.0						
	Wet, (loose), tan, F-M SAND with Silt and scatterd to moderate shell fragments. (Native)	11							
	BOB @ 10.9	12							
		13							

NOTES: A = Archive; B = Bioassay; C = Chemistry Analysis included PCB Aroclors, Organochlorine Pesticides, Semivolatile Organics, Metals (RCRA + Cu + Zn), oil and grease, Total Organic Carbon, and Acid Volatile Sulfides - Simultaneuosly Extracted Metals

- G = Grain Size; GT = Geotechnical testing including Grain Size, Specific Gravity, Moisture Content/Bulk Density P = PCB Congeners
- $^{\star}\,$ In-situ compaction based on linear compaction ratios.
- D = A duplicate was collected at FW-WB-22-CS-6-8.2 and designated FW-WB-61-CS-6-8.2, analyzed for grain size.
- D = A duplicate of FW-WB-22-CS-6-8.2 and designated FW-WB-54-CS-6-8.2 was analyzed for chemistry. MS/MSD was collected at FW-WB-22-CS-6-8.2.



October 2002

Date: 10/19/02 Time: 1326

SEDIMENT CORE: WB-23

System: Cable vibracore Station Description:

Northing: 2321132.03 Depth to Mudline (ft): 1.1 Easting: 2836767.8 Penetration (ft): 11.0 Datum: NAD 83 Indiana West Recovery (ft): 8.0 Mudline Elev. (ft): 578.6 % Recovery: 72

	DESCRIPTI	ON OF	SEDIMENT	ī	ā				
Sample No. and Sample Depth (ft)	Visual Sample Description (In-situ)*	Depth (ft)	Visual Sample Description (Compacted)	Sample No. and Sample Depth (ft)	TESTING	Gravel	Sand	Silt	Clay
	V. wet, (v. soft), black, sandy, clayey SILT with abundant misc. organics; slight to moderate petroleum sheen and odor.	1	V. wet, (v. soft), black, sandy, clayey SILT with abundant misc. organics; slight to moderate petroleum sheen and odor.						
		'		FW-WB-23-CS-0- 2.7	C,GT,P				
FW-WB-23-CS-0- 2.7 (0-3.7')		2		(0-2.7')					
(* *** /									
		3	Texture change, less sewage related materials.	FW-WB-23-CS-2.7- 4.3	A				
	Texture change, less sewage related materials.	4		(2.7-4.3')					
FW-WB-23-CS-2.7- 4.3		5	Moist to damp, (m. stiff to stiff), gray to tan, silty CLAY with fine Sand (CL); peat zones.						
(3.7-5.9')		6	(Native) Tan sand lenses at 5.6 ft below mudline.	FW-WB-23-CS-4.3- 6.5 (4.3-6.5')	C,G				
	Moist to damp, (m. stiff to stiff), gray to tan, silty CLAY with fine Sand (CL); peat zones.	0	Tan sand lenses at 6.2 ft below mudline.						
FW-WB-23-CS-4.3-	(Native)	7	Sandy, silty CLAY.	FW-WB-23-CS-6.5- 7.5 (6.5-7.5')	A				
6.5 (5.9-9')	Tan sand lenses at 7.7 ft below mudline.	8	Back to Silty CLAY with Sand. Piece of bottle and gravel at 7.5 ft below mudline. #						
			BOB @ 8.0'						
	Tan sand lenses at 8.5 ft below mudline.	9							
FW-WB-23-CS-6.5- 7.5 (9-10.4')	Sandy, silty CLAY.								
		10							
	Back to Silty CLAY with Sand. Piece of bottle and gravel at 7.5 ft below mudline. #	11							
	BOB @ 11.0'								
		12							
		13							

NOTES: A = Archive; B = Bioassay; C = Chemistry Analysis included PCB Aroclors, Organochlorine Pesticides, Semivolatile Organics, Metals (RCRA + Cu + Zn), oil and grease, Total Organic Carbon, and Acid Volatile Sulfides - Simultaneuosly Extracted Metals

G = Grain Size; GT = Geotechnical testing including Grain Size, Specific Gravity, Moisture Content/Bulk Density P = PCB Congeners

 $^{\star}\,$ In-situ compaction based on linear compaction ratios.

Material compacted in upper layers. Sand at bottom.

Piece of bottle may have been dragged down while coring.



October 2002

SEDIMENT CORE: WB-24 Date: 10/19/02

Time: 1238

System: Cable vibracore Station Description:

Northing: 2321097.7 Easting: 2836744.8 Datum: NAD 83 Indiana West

Mudline Elev. (ft): 579.2

Depth to Mudline (ft): 0.5 Penetration (ft): 10.7 Recovery (ft): 7.9 % Recovery: 74

	DESCRIPT	ION OF	SEDIMENT	1	g				
Sample No. and Sample Depth (ft)	Visual Sample Description (In-situ)*	Depth (ft)	Visual Sample Description (Compacted)	Sample No. and Sample Depth (ft)	TESTING	Gravel	Sand	Silt	Clay
FW-WB-24-CS-0-2	V. wet, (v. soft), black, clayey, sandy SILT with abundant misc. organics and slight to moderate petroleum sheen and odor.	1	V. wet, (v. soft), black, clayey, sandy SILT with abundant misc. organics and slight to moderate petroleum sheen and odor.	FW-WB-24-CS-0-2	A				
FVV-VVB-24-C3-U-2				(0-2')					
(0-2.7')		2							
			Texture change, sand decreasing misc. organics decreasing.	FW-WB-24-CS-2-					
	Texture change, sand decreasing misc. organics	3		4.2 (2-4.2')	С				
	decreasing.	4							
FW-WB-24-CS-2-			Peat zone.						
4.2 (2.7-5.7')		5	Tan sand lense at 4.6 ft below mudline.	FW-WB-24-CS-4.2- 5.6	С				
	Dark		Wet, (soft), brown, organic, clayey SILT (OH) with peat zones.	(4.2-5.6')					
	Peat zone.	6							
FW-WB-24-CS-4.2- 5.6 (5.7-7.6')	Tan sand lense at 4.6 ft below mudline. Wet, (soft), brown, organic, clayey SILT (OH) with		Wet to moist, (soft), dark brown to brown, clayey SILT with fine Sand and scattered shell fragments and organics (ML/OH). (Native?)	FW-WB-24-CS-5.6- 7.9 (5.6-7.9')	Α				
	peat zones.	7							
		8							
FW-WB-24-CS-5.6-	Wet to moist, (soft), dark brown to brown, clayey SILT with fine Sand and scattered shell fragments and organics (ML/OH). (Native?)		BOB @ 7.9'						
7.9 (7.6-10.7')		9							
		10							
	BOB @ 10.7'	11							
		12							
		13							

NOTES: A = Archive; B = Bioassay; C = Chemistry Analysis included PCB Aroclors, Organochlorine Pesticides, Semivolatile Organics, Metals (RCRA + Cu + Zn), oil and grease, Total Organic Carbon, and Acid Volatile Sulfides - Simultaneuosly Extracted Metals

G = Grain Size; GT = Geotechnical testing including Grain Size, Specific Gravity, Moisture Content/Bulk Density P = PCB Congeners



October 2002

Date: 10/25/02 Time: 1310 System: Cable vibracore

FW-WB-25-CS-

10.1-11.4

(10.5-11.9')

SEDIMENT CORE: WB-25

Station Description: North side of river

Northing: 2321500.97 Easting: 2836232.84 Datum: NAD 83 Indiana West Mudline Elev. (ft): 578.9

Depth to Mudline (ft): 1.0 Penetration (ft): 11.9 Recovery (ft): 11.4 % Recovery: 96

Lab Grain Size (%)

DESCRIPTION OF SEDIMENT FESTING Sample No. and Depth Sample No. and Visual Sample Description (In-situ)* **Visual Sample Description (Compacted)** Sample Depth (ft) Sample Depth (ft) (ft) Silt V. wet, (v. soft) black, clayey, sandy SILT with V. wet, (v. soft) black, clayey, sandy SILT with abundant organics; probable coal tar globules; abundant organics; probable coal tar globules; strong petroleum odor. strong petroleum odor. 1 FW-WB-25-CS-0-FW-WB-25-CS-0-Α 2 (0-4.6')(0-4.4')3 Sandy zone from 3.2 - 3.6 ft below mudline. Sandy zone from 3.3 - 3.8 ft below mudline. 4 Thin, gray silt layer at 4 ft below mudline. Thin, gray silt layer at 4.2 ft below mudline. Wet, (soft), dark olive to black clayey SILT with fine FW-WB-25-CS-4.4-С 5 to medium Sand; trace shell hash throughout; trace FW-WB-25-CS-4.4-Wet, (soft), dark olive to black clayey SILT with (4.4-5.9') fine to medium Sand; trace shell hash throughout; 5.9 trace organics. Peat layer at (4.6-6.2')Peat layer at 5.7 ft below mudline. 5.9 ft below mudline. 6 Wet, (soft), olive, clayey SILT with fine to medium Sand; trace shell hash; trace organics increasing FW-WB-25-CS-5.9-Wet, (soft), olive, clayey SILT with fine to medium with depth. FW-WB-25-CS-5.9-A,GT Sand; trace shell hash; trace organics increasing 7 (6.2-8')with depth. (5.9-7.7')8 Same as above. Same as above. FW-WB-25-CS-7.7 FW-WB-25-CS-7.7-B.C 9 10.1 10.1 (8-10.5') (7.7-10.1') 10

Wet, (loose), olive, silty, fine to medium SAND;

BOB @ 11.4'

some shell hash throughout. (Native?)

NOTES: A = Archive; B = Bioassay; C = Chemistry Analysis included PCB Aroclors, Organochlorine Pesticides, Semivolatile Organics, Metals (RCRA + Cu + Zn), oil and grease, Total Organic Carbon, and Acid Volatile Sulfides - Simultaneuosly Extracted Metals

G = Grain Size; GT = Geotechnical testing including Grain Size, Specific Gravity, Moisture Content/Bulk DensityP = PCB Congeners

11

12

13

* In-situ compaction based on linear compaction ratios.

Wet, (loose), olive, silty, fine to medium SAND;

BOB @ 11.9'

some shell hash throughout. (Native?)



FW-WB-25-CS-

10.1-11.4

(10.1-11.4')

Α

October 2002

Date: 10/25/02 Time: 1330

System: Cable vibracore Station Description: Middle of river.

SEDIMENT CORE: WB-26a

Northing: 2321473.5 Easting: 2836199.2 Datum: NAD 83 Indiana West Mudline Elev. (ft): 578.3

Depth to Mudline (ft): 1.6 Penetration (ft): 5.3 Recovery (ft): 5.1 % Recovery: 96

	DESCRIPTION OF SEDIMENT								
Sample No. and Sample Depth (ft)	Visual Sample Description (In-situ)*	Depth (ft)	Visual Sample Description (Compacted)	Sample No. and Sample Depth (ft)	TESTING	Gravel	Sand	Silt	Clav
		1	V. wet, (v. soft), black, clayey, sandy SILT; extreme odor; extreme staining of CAB liner; coal tar like globules.		F	-		3	,
		2	No Samples Collected from this Core.						
		3							
		4							
		5							
		6	BOB @ 5.1'						
		7							
		8							
		9							
		10							
		11							
		12							
		13							

NOTES: A = Archive; B = Bioassay; C = Chemistry Analysis included PCB Aroclors, Organochlorine Pesticides, Semivolatile Organics, Metals (RCRA + Cu + Zn), oil and grease, Total Organic Carbon, and Acid Volatile Sulfides - Simultaneuosly Extracted Metals

G = Grain Size; GT = Geotechnical testing including Grain Size, Specific Gravity, Moisture Content/Bulk Density P = PCB Congeners

 $^{\star}\,$ In-situ compaction based on linear compaction ratios.

Core was logged but not sampled due to poor penetration.

CORING NOTES: Refusal at 5.3 ft. Coal tar in core catcher. Large sheen and strong odor.



October 2002

Date: 10/25/02 Time: 1406 System: Cable vibracore

SEDIMENT CORE: WB-26b

Northing: 2321464.6 Easting: 2836209.2 Datum: NAD 83 Indiana West Mudline Elev. (ft): 578.7

Depth to Mudline (ft): 1.2 Penetration (ft): 11.3 Recovery (ft): 8.9 % Recovery: 79

Lab Grain Size (%)

Station Description: Middle of river.

	DESCRIPT	ION OF	SEDIMENT		.				l
Sample No. and Sample Depth (ft)	Visual Sample Description (In-situ)*	Depth (ft)	Visual Sample Description (Compacted)	Sample No. and Sample Depth (ft)	TESTING	Gravel	Sand	Silt	Clay
	V. wet, (v. soft), black, clayey, sandy SILT; moderate petroleum odor; heavy sheen; abundant misc. organics throughout; peaty at top.	1	V. wet, (v. soft), black, clayey, sandy SILT; moderate petroleum odor; heavy sheen; abundant misc. organics throughout; peaty at top.		·			<u> </u>	
		2		FW-WB-26-CS-0-5					
FW-WB-26-CS-0-5		3		(0-5')	A				
(0-6.5')		4							
		5							
			Wet, (soft to v. soft) dark olive to black clayey SILT with fine Sand. (ML)	FW-WB-26-CS-5- 6.5 (5-6.5')	Α				
		6	Color change at 6.4 ft below mudline. Sediment becomes lighter and grayer.						
FW-WB-26-CS-5-	Wet, (soft to v. soft) dark olive to black clayey SILT with fine Sand. (ML)	7	Wet, (soft), olive, clayey, sandy SILT; trace shell hash increasing with depth; cinder at base of interval. (ML)	FW-WB-26-CS-6.5- 7.9 (6.5-7.9')	B,C				
6.5 (6.5-8.5')		8	Wet, (loose), olive, silty SAND with trace Clay; some shell hash; mild odor (coal tar). (SM)	FW-WB-26-CS-7.9- 8.9	С				
	Color change at 8.3 ft below mudline. Sediment becomes lighter and grayer. Wet, (soft), olive, clayey, sandy SILT; trace shell			(7.9-8.9')					
FW-WB-26-CS-6.5- 7.9 (8.5-10.3')	hash increasing with depth; cinder at base of interval. (ML)	10	BOB @ 8.9'						
FW-WB-26-CS-7.9- 8.9	Wet, (loose), olive, silty SAND with trace Clay; some shell hash; mild odor (coal tar). (SM)	11							
(10.3-11.3')	BOB @ 11.3'								
		12							
		13							

NOTES: A = Archive; B = Bioassay; C = Chemistry Analysis included PCB Aroclors, Organochlorine Pesticides, Semivolatile Organics, Metals (RCRA + Cu + Zn), oil and grease, Total Organic Carbon, and Acid Volatile Sulfides - Simultaneuosly Extracted Metals

G = Grain Size; GT = Geotechnical testing including Grain Size, Specific Gravity, Moisture Content/Bulk Density P = PCB Congeners

* In-situ compaction based on linear compaction ratios.

Core catcher covered in NAPL (coal tar).



October 2002

Date: 10/25/02 Time: 1435 System: Cable vibracore

SEDIMENT CORE: WB-27

Northing: 2321435.9 Easting: 2836188.2 Datum: NAD 83 Indiana West Mudline Elev. (ft): 578.8

Depth to Mudline (ft): 1.1 Penetration (ft): 11.1 Recovery (ft): 9.3 % Recovery: 84

Station Description: South side of river.

	DESCRIPT	ON OF	SEDIMENT		_o				
Sample No. and Sample Depth (ft)	Visual Sample Description (In-situ)*	Depth (ft)	Visual Sample Description (Compacted)	Sample No. and Sample Depth (ft)	TESTING	Gravel	Sand	Silt	Clay
	V. wet, (soft), black, clayey SILT with fine Sand; abundant misc. organics; strong petroleum odor; probable coal tar globules (top 3.5'); top 6" brown organic matter.	1	V. wet, (soft), black, clayey SILT with fine Sand; abundant misc. organics; strong petroleum odor; probable coal tar globules (top 3.5'); top 6" brown organic matter.						
		2		FW-WB-27-CS-0- 5.4	C,P				
FW-WB-27-CS-0- 5.4 (0-6.5')		3		(0-5.4')					
		4							
		5							
		6	Wet, (soft), olive to dark olive, clayey SILT with fine to medium Sand; trace organics. (ML) Color change at 6.5 ft below mudline.	FW-WB-27-CS-5.4- 6.9 (5.4-6.9')	В,С				
FW-WB-27-CS-5.4-	Wet, (soft), olive to dark olive, clayey SILT with fine to medium Sand; trace organics.(ML)	7	Peat layer at 6.9 ft below mudline. Wet, (soft), olive to brown, clayey SILT with fine to		A,G				
6.9 (6.5-8.3')	Color change at 7.8 ft below mudline.	8	medium Sand; trace shell hash increasing with depth; trace organics. (ML)	8.2 (6.9-8.2')	,-				
FW-WB-27-CS-6.9- 8.2 (8.3-9.8')	Peat layer at 8.3 ft below mudline. Wet, (soft), olive to brown, clayey SILT with fine to medium Sand; trace shell hash increasing with depth; trace organics. (ML)	9	Wet, (loose), olive, silty, SAND with Clay; some shell hash. (SM) (Native?)	FW-WB-27-CS-8.2- 9.3 (8.2-9.3')	A				
FW-WB-27-CS-8.2-	Wet, (loose), olive, silty, SAND with Clay; some	10	BOB @ 9.3'						
9.3 (9.8-11.1')	shell hash. (SM) (Native?)	11							
	BOB @ 11.1'	12							
		13							

NOTES: A = Archive; B = Bioassay; C = Chemistry Analysis included PCB Aroclors, Organochlorine Pesticides, Semivolatile Organics, Metals (RCRA + Cu + Zn), oil and grease, Total Organic Carbon, and Acid Volatile Sulfides - Simultaneuosly Extracted Metals

G = Grain Size; GT = Geotechnical testing including Grain Size, Specific Gravity, Moisture Content/Bulk Density P = PCB Congeners



October 2002

Date: 10/25/02 Time: 1610

System: Cable vibracore Station Description:

SEDIMENT CORE: WB-28

Northing: 2321853.3 Easting: 2835704.5 Datum: NAD 83 Indiana West Mudline Elev. (ft): 578.6

Depth to Mudline (ft): 1.3 Penetration (ft): 10.8 Recovery (ft): 8.9 % Recovery: 82

Lab Grain Size (%)

	DESCRIPT	ON OF	SEDIMENT	ı	<u>o</u>				ı
Sample No. and Sample Depth (ft)	Visual Sample Description (In-situ)*	Depth (ft)	Visual Sample Description (Compacted)	Sample No. and Sample Depth (ft)	TESTING	Gravel	Sand	Silt	Clav
	V. wet, (v. soft), black, sandy, clayey SILT; moderate to strong odor (different from petroleum or coal tar); abundant organics; peaty throughout.	1	V. wet, (v. soft), black, sandy, clayey SILT; moderate to strong odor (different from petroleum or coal tar); abundant organics; peaty throughout.						
	Gravel at 2.6 ft below mudline.	2	Gravel at 2.2 ft below mudline.						
	Graver at 2.0 it below muuline.	3		FW-WB-28-CS-0-7	B,C,GT				
FW-WB-28-CS-0-7 (0-8.4')		4		(0-7')	Р				
		5							
		6							
		7	Tan sand lense with brick and glass from 6.6' to 7.2' below mudline.	FW-WB-28-CS-7-	Α				
		0	Wet, soft, dark olive to brown, clayey, sandy SILT.	7.6 (7-7.6')	A				
FW-WB-28-CS-7- 7.6	Tan sand lense with brick and glass from 7.9' to 8.6' below mudline.	9	Wet, (loose), dark olive, silty SAND with Clay; probable coal tar odor; chunk of wood in core catcher.	FW-WB-28-CS-7.6-8 (7.6-8')	С				
(8.4-9.1') FW-WB-28-CS-7.6-	Wet, soft, dark olive to brown, clayey, sandy SILT.		BOB @ 8.9'	FW-WB-28-CS-8- 8.9 (8-8.9')					
(9.1-9.6') FW-WB-28-CS-8-	Wet, (loose), dark olive, silty SAND with Clay; probable coal tar odor; chunk of wood in core catcher.	10							
8.9 (9.6-10.8')	BOB @ 10.8'	11							
		12							
		13							<u></u>

NOTES: A = Archive; B = Bioassay; C = Chemistry Analysis included PCB Aroclors, Organochlorine Pesticides, Semivolatile Organics, Metals (RCRA + Cu + Zn), oil and grease, Total Organic Carbon, and Acid Volatile Sulfides - Simultaneuosly Extracted Metals

G = Grain Size; GT = Geotechnical testing including Grain Size, Specific Gravity, Moisture Content/Bulk Density P = PCB Congeners

* In-situ compaction based on linear compaction ratios.

Probable coal tar stain on core catcher.

CORING NOTES: Sheen created by coring. Coal tar odor observed.



October 2002

Date: 10/25/02 Time: 1700

System: Cable vibracore Station Description: Center of river.

SEDIMENT CORE: WB-29

Northing: 2321829.4 Easting: 2835697.6 Datum: NAD 83 Indiana West Mudline Elev. (ft): 577.9

Depth to Mudline (ft): 2.0 Penetration (ft): 10.5 Recovery (ft): 8.8 % Recovery: 84

Lab Grain Size (%)

	DESCRIPTI	ON OF	SEDIMENT		_o				
Sample No. and Sample Depth (ft)	Visual Sample Description (In-situ)*	Depth (ft)	Visual Sample Description (Compacted)	Sample No. and Sample Depth (ft)	TESTING	Gravel	Sand	Silt) el
	V. wet, (v. soft), clayey, sandy SILT with abundant misc. organics; finer at base of layer; olive at base of layer; abundant sheen; probable coal tar globules. Worms at 1.1 ft below mudline.	1	V. wet, (v. soft), clayey, sandy SILT with abundant misc. organics; finer at base of layer; olive at base of layer; abundant sheen; probable coal tar globules. Worms at 0.9 ft below mudline.						
		2	Sandy zone; extreme NAPL; trace SLAG.	FW-WB-29-CS-0-5 (0-5')	A				
FW-WB-29-CS-0-5	Sandy zone; extreme NAPL; trace SLAG.	3	Same as 0 to 2.2 ft below mudline.	(0-5)					
(0-6')	Same as 0 to 2.2 ft below mudline.		Peat at 3.4 ft below mudline. Peat at 3.7 ft below mudline.						
	Peat at 4 ft below mudline.	4							
	Peat at 4.4 ft below mudline.	5	Color change at 4.6 ft below mudline; black to dark olive .						
	Color change at 5.5 ft below mudline; black to dark olive .	6	Wet, (soft), dark olive, clayey SILT with fine to medium Sand; trace SLAG. (ML)	FW-WB-29-CS-5- 6.6	С				
	Wet, (soft), dark olive, clayey SILT with fine to medium Sand; trace SLAG. (ML)			(5-6.6')					
FW-WB-29-CS-5- 6.6 (6-7.9')		7	Wet, (loose), silty SAND with Clay. (SM) Shell hash from 6.6 ft to 6.8 ft below mudline. Shell hash from 7.6 ft to 7.9 ft below mudline.	FW-WB-29-CS-6.6- 8.8 (6.6-8.8')	B,C,GT				
	Shell hash from 7.9 ft to 8.1 ft below mudline.	8	NAPL at 7.9 ft below mudline.						
FW-WB-29-CS-6.6- 8.8	Wet, (loose), silty SAND with Clay. (SM)	9							
(7.9-10.5')	Shell hash from 9.0 ft to 9.4 ft below mudline. NAPL at 9.4 ft below mudline.		BOB @ 8.8'						
		10							
	BOB @ 10.5'	11							
		12							
		13							

NOTES: A = Archive; B = Bioassay; C = Chemistry Analysis included PCB Aroclors, Organochlorine Pesticides, Semivolatile Organics, Metals (RCRA + Cu + Zn), oil and grease, Total Organic Carbon, and Acid Volatile Sulfides - Simultaneuosly Extracted Metals

G = Grain Size; GT = Geotechnical testing including Grain Size, Specific Gravity, Moisture Content/Bulk Density P = PCB Congeners



October 2002

Date: 10/25/02 Time: 1710

System: Cable vibracore Station Description: Center of river.

SEDIMENT CORE: WB-29geo

Northing: 2321829.4 Easting: 2835697.6 Datum: NAD 83 Indiana West Mudline Elev. (ft): 577.9

Depth to Mudline (ft): 2.0 Penetration (ft): 10.9 Recovery (ft): 8.4 % Recovery: 77

	DESCRIP	TION OF	SEDIMENT		စ္				
Sample No. and Sample Depth (ft)	Visual Sample Description (In-situ)*	Depth (ft)	Visual Sample Description (Compacted)	Sample No. and Sample Depth (ft)	TESTING	Gravel	Sand	Silt	٥
		1							
		2							
		3							
		4							
		5	Wet, (soft), dark olive, clayey SILT with fine to		uu,co				
		6	medium Sand; NAPL present.	WB-29 5-6.4 (5-6.4')	00,00				
WB-29 5-6.4	Wet, (soft), dark olive, clayey SILT with fine to medium Sand; NAPL present.	7	Headspace ranged from 0.0' to 0.005'.						
(6.5-8.3')	Headspace ranged from 0.0' to 0.005'.	_	Wet, (loose), silty SAND with Clay; some shell hash; NAPL present. (SM)	WB-29 6.6-7.6 (6.6-7.6')	DS				
	Treadspace ranged non-old to 0.000.	8	Headspace ranged from 0.01' to 0.004'.						
WB-29 6.6-7.6 (8.6-9.9')	Wet, (loose), silty SAND with Clay; some shell hash; NAPL present. (SM)	9	BOB @ 8.4'						
	Headspace ranged from 0.01' to 0.004'.	- 10							
	BOB @ 10.9'	- 11							
		12							
		13							

NOTES: DS = Direct Shear Testing; **UU** = UU Triaxial Shear Testing; **CO** = Consolidation Testing.

Headspace measurements taken in tenths of a foot from the top of the sediment to the top of the aluminum pipe.



^{*} In-situ compaction based on linear compaction ratios.

October 2002

Date: 10/25/02 Time: 1745 System: Cable vibracore

SEDIMENT CORE: WB-30

Northing: 2321816.9 Easting: 2835690.26 Datum: NAD 83 Indiana West Mudline Elev. (ft): 578.4

Depth to Mudline (ft): 1.5 Penetration (ft): 10.4 Recovery (ft): 8.9 % Recovery: 86

Station Description: South side of river.

	DESCRIPT	ON OF	SEDIMENT		_O				
Sample No. and Sample Depth (ft)	Visual Sample Description (In-situ)*	Depth (ft)	Visual Sample Description (Compacted)	Sample No. and Sample Depth (ft)	TESTING	Gravel	Sand	Silt	Clay
FW-WB-30-CS-0- 1.2 (0-1.4')	V. wet, (v. soft), black, clayey, sandy SILT; abundant misc. organics; sheen; strong odor.	1	V. wet, (v. soft), black, clayey, sandy SILT; abundant misc. organics; sheen; strong odor.	FW-WB-30-CS-0- 1.2 (0-1.2')	A				
FW-WB-30-CS-1.2- 2.7	Wet, (loose), tan, silty SAND with black striations throughout.	2	Wet, (loose), tan, silty SAND with black striations throughout.	FW-WB-30-CS-1.2- 2.7 (1.2-2.7')	A				
(1.4-3.2') FW-WB-30-CS-2.7-	NASI AND AND AND AND AND AND AND AND AND AND	3	Same as above; heavy NAPL staining from 2.7' to 3.1' below mudline.	FW-WB-30-CS-2.7 ² 3.1 (2.7-3.1')	Α				
3.1 (3.2-3.6') FW-WB-30-CS-3.1- 4.9 (3.6-5.7')	Same as above; heavy NAPL staining from 3.2' to 3.6' below mudline. Wet, (soft), clayey SILT with fine to medium Sand; increasing organics with depth; peaty at bottom; dark gray to dark olive at base of interval. (ML)	<u>4</u> 5	Wet, (soft), clayey SILT with fine to medium Sand; increasing organics with depth; peaty at bottom; dark gray to dark olive at base of interval. (ML)	FW-WB-30-CS-3.1- 4.9 (3.1-4.9')	в,с				
		6	Wet, (soft), dark brown, clayey SILT with fine to medium Sand; abundant organics (peat); trace shell hash. (ML)	FW-WB-30-CS-4.9- 5.8 (4.9-5.8')	A				
FW-WB-30-CS-4.9- 5.8 (5.7-6.8')	Wet, (soft), dark brown, clayey SILT with fine to medium Sand; abundant organics (peat); trace shell hash. (ML)	0	Wet, (soft), olive, clayey SILT with fine to medium Sand; some organics; trace shell hash. (ML)	FW-WB-30-CS-5.8- 6.6 (5.8-6.6')	C,GT,P				
FW-WB-30-CS-5.8- 6.6 (6.8-7.7')	Wet, (soft), olive, clayey SILT with fine to medium Sand; some organics; trace shell hash. (ML)	7	Same as above with NAPL pockets throughout; fining downward.	FW-WB-30-CS-6.6- 7.9 (6.6-7.9')	A				
FW-WB-30-CS-6.6- 7.9 (7.7-9.2')	Same as above with NAPL pockets throughout; fining downward.	9	Wet, (loose), olive, silty SAND with Clay; some shell hash; NAPL globules throughout. (SM)	FW-WB-30-CS-7.9- 8.9 (7.9-8.9')	С				
FW-WB-30-CS-7.9- 8.9 (9.2-10.4')	Wet, (loose), olive, silty SAND with Clay; some shell hash; NAPL globules throughout. (SM)	10	BOB @ 8.9'						
	BOB @ 10.4'	11							
		12							
		13							

NOTES: A = Archive; B = Bioassay; C = Chemistry Analysis included PCB Aroclors, Organochlorine Pesticides, Semivolatile Organics, Metals (RCRA + Cu + Zn), oil and grease, Total Organic Carbon, and Acid Volatile Sulfides - Simultaneuosly Extracted Metals

G = Grain Size; GT = Geotechnical testing including Grain Size, Specific Gravity, Moisture Content/Bulk Density P = PCB Congeners



October 2002

Date: 10/19/02 Time: 1035

System: Cable vibracore Station Description: North side of river.

SEDIMENT CORE: WB-31

Northing: 2321097.7 Easting: 2836744.8 Datum: NAD 83 Indiana West Mudline Elev. (ft): 577.3

Depth to Mudline (ft): 0.5 Penetration (ft): 10.4 Recovery (ft): 9.2 % Recovery: 88

Lab Grain Size (%)

	DESCRIPT	ON OF	SEDIMENT	r	_o				l
Sample No. and Sample Depth (ft)	Visual Sample Description (In-situ)*	Depth (ft)	Visual Sample Description (Compacted)	Sample No. and Sample Depth (ft)	TESTING	Gravel	Sand	Silt	Clav
FW-WB-31-CS-0- 2.8	V. wet, (v. soft), black, clayey, sandy SILT with petroleum odor and slight sheen; organic debris.	1	V. wet, (v. soft), black, clayey, sandy SILT with petroleum odor and slight sheen; organic debris.	FW-WB-31-CS-0- 2.5 (0-2.5')	A				
(0-2.5')	Clay increases at 1.7 ft below mudline.	2	Clay increases at 1.5 ft below mudline.						
		3	Change in consistency.						
	Change in consistency. Wet, (soft), black, clayey SILT with fine Sand and petroleum sheen and odor (ML); a few peat zones with depth.	4	Wet, (soft), black, clayey SILT with fine Sand and petroleum sheen and odor (ML); a few peat zones with depth.						
		5		FW-WB-31-CS-4- 6.5 (4-6.5')	в,с				
FW-WB-31-CS-4- 6.5 (4.5-7.3')		6							
		7	Wet to moist, (soft), olive brown, clayey SILT with fine Sand (ML). (Native?)	FW-WB-31-CS-6.5- 7.8 (6.5-7.8')	Α				
7.8	Wet to moist, (soft), olive brown, clayey SILT with fine Sand (ML). (Native?)	8							
(7.3-8.8')		9	Wet, (loose), tan, silty, fine to medium SAND with moderate shell fragments (SM). (Native)	FW-WB-31-CS-7.8- 9.2 (7.8-9.2')	C,G				
FW-WB-31-CS-7.8- 9.2 (8.8-10.4')	Wet, (loose), tan, silty, fine to medium SAND with moderate shell fragments (SM). (Native)	10	BOB @ 9.2'						
	BOB @ 10.4'	11							
		12							
		13							

NOTES: A = Archive; B = Bioassay; C = Chemistry Analysis included PCB Aroclors, Organochlorine Pesticides, Semivolatile Organics, Metals (RCRA + Cu + Zn), oil and grease, Total Organic Carbon, and Acid Volatile Sulfides - Simultaneuosly Extracted Metals

G = Grain Size; GT = Geotechnical testing including Grain Size, Specific Gravity, Moisture Content/Bulk Density P = PCB Congeners



October 2002

SEDIMENT CORE: WB-32

Date: 10/19/02 Time: 1005

Station Description:

System: Cable vibracore

Northing: 2322277.2 Depth to Mudline (ft): 0.0 Easting: 2834839.4 Penetration (ft): 10.8 Recovery (ft): 6.8 Datum: NAD 83 Indiana West Mudline Elev. (ft): % Recovery: 63

	DESCRIPT	ION OF	SEDIMENT		စ				l
Sample No. and Sample Depth (ft)	Visual Sample Description (In-situ)*	Depth (ft)	Visual Sample Description (Compacted)	Sample No. and Sample Depth (ft)	TESTING	Gravel	Sand	Silt	Clav
FW-WB-CS-0-2	Wet, (loose), gray to black, silty, fine to medium SAND with woody debris; misc. organics; petroleum sheen (slight) and odor.	1	Wet, (loose), gray to black, silty, fine to medium SAND with woody debris; misc. organics; petroleum sheen (slight) and odor.	FW-WB-CS-0-2 (0-2')	B,C,GT				
(0-3.2')									1
(0-3.2)		2							
		3	Wet, (soft), black, clayey SILT with Sand; misc. organics; petroleum sheen and odor. (ML/OH)	FW-WB-CS-2-4 (2-4')	С,СТ				
	Wet, (soft), black, clayey SILT with Sand; misc. organics; petroleum sheen and odor. (ML/OH)	4							
FW-WB-CS-2-4 (3.2-6.4')		5	Wet, (soft), black, clayey SILT with Sand and extensive NAPL throughout. (ML)	FW-WB-CS-4-6.4	A				
		6		(4-6.4')					
	Wet, (soft), black, clayey SILT with Sand and	- 	Wet, (soft), gray to brown, clayey SILT. (ML)						
	extensive NAPL throughout. (ML)	7	BOB @ 6.8'						
FW-WB-CS-4-6.4		8							
(6.4-10.2')		9							
		10							
	Wet, (soft), gray to brown, clayey SILT. (ML)	11							
	BOB @ 10.8'	12							
		13							

NOTES: A = Archive; B = Bioassay; C = Chemistry Analysis included PCB Aroclors, Organochlorine Pesticides, Semivolatile Organics, Metals (RCRA + Cu + Zn), oil and grease, Total Organic Carbon, and Acid Volatile Sulfides - Simultaneuosly Extracted Metals

G = Grain Size; GT = Geotechnical testing including Grain Size, Specific Gravity, Moisture Content/Bulk Density P = PCB Congeners

 $^{\star}\,$ In-situ compaction based on linear compaction ratios.

Extent of NAPL appears to be limited to 6.4'.

Not enough sample in catcher for analysis.

Decided to accept core even though recovery was poor because of access and NAPL.

CORIN NOTES: No overlying water.



October 2002

SEDIMENT CORE: WB-33 Date: 10/19/02

Time: 0950 System: cable vibracore Northing: 2322249.3 Easting: 2834826.4 Datum: NAD 83 Indiana West

Mudline Elev. (ft):

Depth to Mudline (ft): 0.0 Penetration (ft): 11.0 Recovery (ft): 7.7 % Recovery: 70

Station Description: South edge of river.

	DESCRIPT	ION OF	SEDIMENT		(n				
Sample No. and Sample Depth (ft)	Visual Sample Description (In-situ)*	Depth (ft)	Visual Sample Description (Compacted)	Sample No. and Sample Depth (ft)	TESTING	Gravel	Sand	Silt	Clay
FW-WB-33-CS-0-2	V. wet, (v. soft), black, sandy SILT with petroleum sheen and odor; misc. organics.	1	V. wet, (v. soft), black, sandy SILT with petroleum sheen and odor; misc. organics.	FW-WB-33-CS-0-2 (0-2')	A				
(0-2.9')		2	grading to	, ,					1
FW-WB-33-CS-2-4		3	Wet to moist, (soft), black to brown, sandy, clayey, SILT (ML/OH) with petroleum odor and misc. organics; bands of brown(olive) to black with depth	, ,	A				
(2.9-5.7')		4	but petroleum odor appears entire.						
	grading to	5		FW-WB-33-CS-4-6 (4-6')	С				
FW-WB-33-CS-4-6 (5.7-8.6')	Wet to moist, (soft), black to brown, sandy, clayey,	7		FW-WB-33-CS-6- 7.4 (6-7.4')	С				
	SILT (ML/OH) with petroleum odor and misc. organics; bands of brown(olive) to black with depth but petroleum odor appears entire.	8	Wet, loose, tan to gray, silty, fine to medium SAND (SM) with shell fragments. (Native) BOB @ 7.7'						
FW-WB-33-CS-6- 7.4 (8.6-10.6')		9							
	Wet, loose, tan to gray, silty, fine to medium SAND (SM) with shell fragments. (Native)	11							
	BOB @ 11.0'	12							
		13							

NOTES: A = Archive; B = Bioassay; C = Chemistry Analysis included PCB Aroclors, Organochlorine Pesticides, Semivolatile Organics, Metals (RCRA + Cu + Zn), oil and grease, Total Organic Carbon, and Acid Volatile Sulfides - Simultaneuosly Extracted Metals

G = Grain Size; GT = Geotechnical testing including Grain Size, Specific Gravity, Moisture Content/Bulk Density P = PCB Congeners

 $^{\star}\,$ In-situ compaction based on linear compaction ratios.

A lot of compaction but because of access problems and little disturbance, decided to accept core.

Did not reach "clean" material until catcher which appeared to be clean, but did not have enough material to sample.

CORING NOTES: No overlying water at core location.



October 2002

Date: 10/21/02 Time: 1200

SEDIMENT CORE: WB-34

Northing: 2322548.4 Easting: 2834461.3 Datum: NAD 83 Indiana West

Mudline Elev. (ft): 577.4

Depth to Mudline (ft): 0.4 Penetration (ft): 11.0 Recovery (ft): 8.7

System: Cable vibracore Station Description: North side of river. % Recovery: 79

Lab Grain Size (%)

	DESCRIPT	ION OF	SEDIMENT		(n				
Sample No. and Sample Depth (ft)	Visual Sample Description (In-situ)*	Depth (ft)	Visual Sample Description (Compacted)	Sample No. and Sample Depth (ft)	TESTING	Gravel	Sand	Silt	Clay
FW-WB-34-CS-0- 1.7 (0-2.2')	V. wet, (v. soft), black, sandy, clayey, SILT with misc. organics (abundant); slight petroleum sheen and moderate odor.	1	V. wet, (v. soft), black, sandy, clayey, SILT with misc. organics (abundant); slight petroleum sheen and moderate odor.	FW-WB-34-CS-0- 1.7 (0-1.7')	A				
FW-WB-34-CS-1.7- 4.6 (2.2-6')	V. wet, (soft), dark brown clayey, sandy SILT with misc. organics (more at top) grades to sandy, clayey SILT (ML/OH).	3 4	V. wet, (soft), dark brown clayey, sandy SILT with misc. organics (more at top) grades to sandy, clayey SILT (ML/OH).	FW-WB-34-CS-1.7- 4.6 (1.7-4.6')	В,С,Р				
	Wet, (soft), dark tan, clayey SILT; trace shells	5	Wet, (soft), dark tan, clayey SILT; trace shells (more than below). (ML) (Native?)	FW-WB-34-CS-4.6- 6.4 (4.6-6.4')	C,G				
FW-WB-34-CS-4.6- 6.4 (6-8.3')	(more than below). (ML) (Native?)	7 8	Moist, (medium dense), tan, SAND, trace Silt; laminated; trace shells and trace wood (at top and throughout) (SW). (Native)	FW-WB-34-CS-6.4- 8.7 (6.4-8.7')	B,C,G				
FW-WB-34-CS-6.4- 8.7 (8.3-11')	Moist, (medium dense), tan, SAND, trace Silt; laminated; trace shells and trace wood (at top and throughout) (SW). (Native)	9 10	BOB @ 8.7'						
	BOB @ 11.0'	11							
		13							

NOTES: A = Archive; B = Bioassay; C = Chemistry Analysis included PCB Aroclors, Organochlorine Pesticides, Semivolatile Organics, Metals (RCRA + Cu + Zn), oil and grease, Total Organic Carbon, and Acid Volatile Sulfides - Simultaneuosly Extracted Metals

G = Grain Size; GT = Geotechnical testing including Grain Size, Specific Gravity, Moisture Content/Bulk Density P = PCB Congeners



October 2002

Date: 10/21/02 Time: 1450

System: Cable vibracore Station Description: North side of river.

SEDIMENT CORE: WB-34geo

Northing: 2322548.4 Easting: 2834461.3 Datum: NAD 83 Indiana West Mudline Elev. (ft): 577.4

Depth to Mudline (ft): 0.4 Penetration (ft): 10.9 Recovery (ft): 8.6 % Recovery: 79

	DESCRIPT	ION OF	SEDIMENT		(2)				
Sample No. and Sample Depth (ft)	Visual Sample Description (In-situ)*	Depth (ft)	Visual Sample Description (Compacted)	Sample No. and Sample Depth (ft)	TESTING	Gravel	Sand	Silt	Clay
		1							
		2	V. wet, (soft), dark brown clayey, sandy SILT with						
. <u> </u>	V. wet, (soft), dark brown clayey, sandy SILT with misc. organics (more at top) grades to sandy, clayey SILT (ML/OH).	3	misc. organics (more at top) grades to sandy, clayey SILT (ML/OH).		UU,CO				
	Geotech sample 2 - 3.5	4	Geotech sample 2 - 3.5						
		5	Wet, (soft), dark tan, clayey SILT; trace shells						
		6	(more than below). (Native?) Geotech sample 5 - 6.3		UU,CO				
	Wet, (soft), dark tan, clayey SILT; trace shells (more than below). (Native?) Geotech sample 5 - 6.3	7	Moist, (medium dense), tan, SAND, trace Silt; laminated; trace shells and trace wood (at top and throughout) (SW). (Native)		DS				
		8	Geotech sample 6.3 - 7.9						
	Moist, (medium dense), tan, SAND, trace Silt; laminated; trace shells and trace wood (at top and throughout) (SW). (Native)		BOB @ 8.6'						
	Geotech sample 6.3 - 7.9	9	BOB (@ 6.0						
		10							
	BOB @ 10.9'	11							
		12							
		13							

NOTES: DS = Direct Shear Testing; UU = UU Triaxial Shear Testing; CO = Consolidation Testing.



^{*} In-situ compaction based on linear compaction ratios.

October 2002

Date: 10/21/02 Time: 1125

System: Cable vibracore Station Description: Center of river.

SEDIMENT CORE: WB-35

Northing: 2322523.8 Easting: 2834452.8 Datum: NAD 83 Indiana West Mudline Elev. (ft): 577.6

Depth to Mudline (ft): 0.2 Penetration (ft): 11.3 Recovery (ft): 9.2 % Recovery: 81

	DESCRIPT	ON OF	SEDIMENT		ទ្វ				ı
Sample No. and Sample Depth (ft)	Visual Sample Description (In-situ)*	Depth (ft)	Visual Sample Description (Compacted)	Sample No. and Sample Depth (ft)	TESTING	Gravel	Sand	Silt	Clay
FW-WB-35-CS-0- 1.5 (0-1.8')	V. wet, (loose), black, silty, fine to medium SAND with petroleum sheen and odor; misc. organics.	1	V. wet, (loose), black, silty, fine to medium SAND with petroleum sheen and odor; misc. organics.	FW-WB-35-CS-0- 1.5 (0-1.5')	A				
FW-WB-35-CS-1.5- 5 (1.8-6.2')	V. wet to wet, (v. soft), black, clayey SILT with Sand; abundant misc. organics and fibrous organics (OH).	3	V. wet to wet, (v. soft), black, clayey SILT with Sand; abundant misc. organics and fibrous organics (OH).	FW-WB-35-CS-1.5- 5 (1.5-5')	В,С				
	Wet to moist, (soft), black to gray to dark olive,	6	Wet to moist, (soft), black to gray to dark olive, clayey SILT with Sand; less sewage related materials (OH).	FW-WB-35-CS-5-7 (5-7')	С				
FW-WB-35-CS-5-7 (6.2-8.6')	clayey SILT with Sand; less sewage related materials (OH).	8	Grading to Olive brown shell fragments (ML). (Native)	FW-WB-35-CS-7- 8.6 (7-8.6')	A				
FW-WB-35-CS-7- 8.6 (8.6-10.6')	Grading to Olive brown shell fragments (ML). (Native)	9	Wet, loose, gray to olive, sandy, fine to medium Gravel with Silt and shell frags (GM). BOB @ 9.2'	FW-WB-35-CS-8.6- 9.2 (8.6-9.2')	A				
FW-WB-35-CS-8.6- 9.2 (9.2-11.3')	Wet, loose, gray to olive, sandy, fine to medium Gravel with Silt and shell frags (GM).	11							
(9.2-11.3)	BOB @ 11.3'	12							

NOTES: A = Archive; B = Bioassay; C = Chemistry Analysis included PCB Aroclors, Organochlorine Pesticides, Semivolatile Organics, Metals (RCRA + Cu + Zn), oil and grease, Total Organic Carbon, and Acid Volatile Sulfides - Simultaneuosly Extracted Metals

G = Grain Size; GT = Geotechnical testing including Grain Size, Specific Gravity, Moisture Content/Bulk Density P = PCB Congeners



October 2002

SEDIMENT CORE: WB-36 Date: 10/21/02 Time: 1100

System: Cable vibracore Station Description: South side of river.

Northing: 2322497.3 Easting: 2834440.9 Datum: NAD 83 Indiana West Mudline Elev. (ft): 577.7

Depth to Mudline (ft): 0.1 Penetration (ft): 11.3 Recovery (ft): 9.3 % Recovery: 79

	DESCRIPTI	ON OF	SEDIMENT		ត្				i
Sample No. and Sample Depth (ft)	Visual Sample Description (In-situ)*	Depth (ft)	Visual Sample Description (Compacted)	Sample No. and Sample Depth (ft)	TESTING	Gravel	Sand	Silt	
FW-WB-36-CS-0- 2.2	V. wet, (v. soft), black, clayey, sandy SILT with abundant misc. organics; petroleum sheen and slight odor; large gravels in upper 1.5'.	1	V. wet, (v. soft), black, clayey, sandy SILT with abundant misc. organics; petroleum sheen and slight odor; large gravels in upper 1.5'.	FW-WB-36-CS-0- 2.2 (0-2.2')	в,с				
(0-2.7')		2							
		3	Wet, (v. soft), black, clayey SILT with Sand; less misc. organics.						
FW-WB-36-CS-2.2- 4.4 (2.7-5.4')	Wet, (v. soft), black, clayey SILT with Sand; less misc. organics.	4		FW-WB-36-CS-2.2- 4.4 (2.2-4.4')	Α				
		5	NAPL pocket in sandy fine to medium gravel matrix.	FW-WB-36-CS-4.4- 5.1 (4.4-5.1')	А				
FW-WB-36-CS-4.4- 5.1 (5.4-6.2')	NAPL pocket in sandy fine to medium gravel matrix.	6	Same as above. Wet to moist, (soft), olive brown, clayey SILT with fine Sand and abundant to moderate fine organics and trace shell frags (OH).						
FW-WB-36-CS-5.5-	Same as above. Wet to moist, (soft), olive brown, clayey SILT with fine Sand and abundant to moderate fine organics and trace shell frags (OH).	7		FW-WB-36-CS-5.5- 8 (5.5-8')	С				
8 (6.7-9.8')		8	Wet, (loose), tan to brown, silty, fine to medium SAND (SM). (Native)	FW-WB-36-CS-8- 8.5	Α				
		9	Wet, (loose), tan to brown, sandy, fine to medium GRAVEL with Silt (GM). (Native)	(8-8.5') FW-WB-36-CS-8.5-,	Α				
FW-WB-36-CS-8-\			Moist to damp, (stiff), gray, silty CLAY (CL). BOB @ 9.3'	9.1 (8.5-9.1')	Α				<u> </u>
8.5 (9.8-10.4')	Wet, (loose), tan to brown, silty, fine to medium SAND (SM). (Native)	10		FW-WB-36-CS-9.1- 9.3]
FW-WB-36-CS-8.5- 9.1 (10.4-11.1')	Wet, (loose), tan to brown, sandy, fine to medium GRAVEL with Silt (GM). (Native)	11		(9.1-9.3')					
	Moist to damp, (stiff), gray, silty CLAY (CL).								l
FW-WB-36-CS-9.1- 9.3 (11.1-11.3')	BOB @ 11.3'	12							
		13							

NOTES: A = Archive; B = Bioassay; C = Chemistry Analysis included PCB Aroclors, Organochlorine Pesticides, Semivolatile Organics, Metals (RCRA + Cu + Zn), oil and grease, Total Organic Carbon, and Acid Volatile Sulfides - Simultaneuosly Extracted Metals

G = Grain Size; GT = Geotechnical testing including Grain Size, Specific Gravity, Moisture Content/Bulk Density P = PCB Congeners



October 2002

SEDIMENT CORE: WB-37 Northing: 23223307.9 Depth to Mudline (ft): 0.3 Date: 10/27/02 Easting: 2832863.0 Penetration (ft): 11.0 Time: 1420 Datum: NAD 83 Indiana West Recovery (ft): 9.7 System: Cable vibracore Mudline Elev. (ft): 577.1 % Recovery: 88

Station Description: North side of river - relocated due to debris and bridge.

	DESCRIPT	ION OF	SEDIMENT						
Sample No. and Sample Depth (ft)	Visual Sample Description (In-situ)*	Depth (ft)	Visual Sample Description (Compacted)	Sample No. and Sample Depth (ft)	TESTING	Gravel	Sand	Silt	Clay
	V. wet, (v. soft), black, clayey SILT with fine to medium Sand; extremely strong odor (different from petroleum odor); high sheen and probable coal tar globules.	1	V. wet, (v. soft), black, clayey SILT with fine to medium Sand; extremely strong odor (different from petroleum odor); high sheen and probable coal tar globules.						
		2		FW-WB-37-CS-0-5	C,P				
FW-WB-37-CS-0-5		3		(0-5')					1
(0-5.7')		4	Slightly less black and less sheen below 3.7 ft.						
	Slightly less black and less sheen below 4.2 ft.	5	Wet, (soft), dark olive, clayey SILT with fine to						
	Wet (act) ded alice along Oll Toith for the	6	medium Sand; trace shell hash increases with depth; extremely strong odor as above.	FIN IND 27 00 5					
FW-WB-37-CS-5- 7.8 (5.7-8.8')	Wet, (soft), dark olive, clayey SILT with fine to medium Sand; trace shell hash increases with depth; extremely strong odor as above.	7		FW-WB-37-CS-5- 7.8 (5-7.8')	C,G				
		8	Wet, (loose to medium dense), dark tan to gray, silty, fine to coarse SAND with trace Clay (SW); some shell hash; coarsening downwards; strong odor as above. (Native)	FW-WB-37-CS-7.8- 9.1 (7.8-9.1')	С,В				
FW-WB-37-CS-7.8- 9.1 (8.8-10.3')	Wet, (loose to medium dense), dark tan to gray, silty, fine to coarse SAND with trace Clay (SW); some shell hash; coarsening downwards; strong odor as above. (Native)	10	Damp, (firm), tan CLAY with Silt and trace fine Sand (CL) (Native).	FW-WB-37-CS-9.1- 9.6 (9.1-9.6')	Α				
FW-WB-37-CS-9.1- 9.6			BOB @ 9.7'						
(10.3-11')	Damp, (firm), tan CLAY with Silt and trace fine Sand (CL) (Native).	11							
	BOB @ 11.0'								
		12							
		13							

NOTES: A = Archive; B = Bioassay; C = Chemistry Analysis included PCB Aroclors, Organochlorine Pesticides, Semivolatile Organics, Metals (RCRA + Cu + Zn), oil and grease, Total Organic Carbon, and Acid Volatile Sulfides - Simultaneuosly Extracted Metals

G = Grain Size; GT = Geotechnical testing including Grain Size, Specific Gravity, Moisture Content/Bulk Density P = PCB Congeners

CORING NOTES: Refusal at 11' and large sheen appeared during coring.



^{*} In-situ compaction based on linear compaction ratios.

October 2002

Date: 10/24/02 Time: 1500 System: Cable vibracore

SEDIMENT CORE: WB-38

Northing: 2323294.9 Easting: 2832856.0 Datum: NAD 83 Indiana West Mudline Elev. (ft): 575.9

Depth to Mudline (ft): 1.5 Penetration (ft): 10.4 Recovery (ft): 9.4 % Recovery: 90

Station Description: Center of river.

	DESCRIPT	ION OF	SEDIMENT		_O				
Sample No. and Sample Depth (ft)	Visual Sample Description (In-situ)*	Depth (ft)	Visual Sample Description (Compacted)	Sample No. and Sample Depth (ft)	TESTING	Gravel	Sand	Silt	Clay
	V. wet, (v. soft), black, sandy, clayey SILT; extremely strong odor (different from petroleum odor); abundant misc. organics throughout; coal ta globules; extreme sheen and oil NAPL.	1	V. wet, (v. soft), black, sandy, clayey SILT; extremely strong odor (different from petroleum odor); abundant misc. organics throughout; coal ta globules; extreme sheen and oil NAPL.						
		2		FW-WB-38-CS-0-5	A				
FW-WB-38-CS-0-5		3		(0-5')					
(0-5.5')		4							
			Slightly less black.						
FW-WB-38-CS-5-	Slightly less black. Peaty at base. Wet, (soft), dark olive, clayey SILT with fine to medium Sand; trace shell hash; very strong strange odor as above;	6	Peaty at base. Wet, (soft), dark olive, clayey SILT with fine to medium Sand; trace shell hash; very strong strange odor as above;	FW-WB-38-CS-5- 7.2 (5-7.2')	A				
7.2 (5.5-7.9')		7	Slightly more shell hash.	(61.2)					
FW-WB-38-CS-7.2- 8.4	Slightly more shell hash. Wet, (loose), dark tan, silty SAND with Clay. (SM)	. 8	Wet, (loose), dark tan, silty SAND with Clay.	FW-WB-38-CS-7.2- 8.4 (7.2-8.4')	C,G				
(7.9-9.2')	(Native)	9	(Native) Moist, (v. firm), tan CLAY with Silt and trace fine Sand (CL) (Native)	FW-WB-38-CS-8.4- 9.4 (8.4-9.4')	С				
FW-WB-38-CS-8.4- 9.4 (9.2-10.4')	Moist, (v. firm), tan CLAY with Silt and trace fine Sand (CL) (Native).	10	BOB @ 9.4'						
	BOB @ 10.4'	11							
		12							
		13							L

NOTES: A = Archive; B = Bioassay; C = Chemistry Analysis included PCB Aroclors, Organochlorine Pesticides, Semivolatile Organics, Metals (RCRA + Cu + Zn), oil and grease, Total Organic Carbon, and Acid Volatile Sulfides - Simultaneuosly Extracted Metals

G = Grain Size; GT = Geotechnical testing including Grain Size, Specific Gravity, Moisture Content/Bulk Density P = PCB Congeners

* In-situ compaction based on linear compaction ratios.

CORING NOTES: Refusal at 10.4 ft.

> Large sheen created by coring. Coal tar on core tube.



October 2002

Date: 10/24/02 Time: 1550

System: Cable vibracore

Station Description: South side of river.

SEDIMENT CORE: WB-39

Northing: 2323271.3 Easting: 2832860.4 Datum: NAD 83 Indiana West Mudline Elev. (ft): 575.9

Depth to Mudline (ft): 1.5 Penetration (ft): 10.0 Recovery (ft): 8.3 % Recovery: 83

Lab Grain Size (%)

	DESCRIPT	ION OF	SEDIMENT		ភ្				i
Sample No. and Sample Depth (ft)	Visual Sample Description (In-situ)*	Depth (ft)	Visual Sample Description (Compacted)	Sample No. and Sample Depth (ft)	TESTING	Gravel	Sand	Silt	1
	V. wet, (v. soft), black, clayey SILT with fine to medium Sand; strong petroleum odor, high sheen; abundant organics throughout.	1	V. wet, (v. soft), black, clayey SILT with fine to medium Sand; strong petroleum odor, high sheen; abundant organics throughout.	FW-WB-39-CS-0-	A				
FW-WB-39-CS-0- 3.1 (0-3.7')		2		3.1 (0-3.1')					
		3	Dark olive at base.						
	Dark olive at base.	4	Wet, (soft), dark olive, clayey, sandy SILT (ML); trace shell hash increasing at base; trace organics		B,C,GT				
FW-WB-39-CS-3.1-	Wet, (soft), dark olive, clayey, sandy SILT (ML); trace shell hash increasing at base; trace organics (peaty).		(peaty). Peat layer at 4.5 ft below mudline.	(3.1-5.3')					
5.3 (3.7-6.4')	Peat layer at 5.4 ft below mudline.	5	Sandier at base.						
	Sandier at base.	6	Moist to wet, (loose to dense), tan, silty, SAND with trace Clay (SM); abundant shell hash concentrated in middle. (Native)	FW-WB-39-CS-5.3- 7.7	С				
FW-WB-39-CS-5.3-	Moist to wet, (loose to dense), tan, silty, SAND with trace Clay (SM); abundant shell hash concentrated in middle. (Native)	7		(5.3-7.7') MS/MSD					
7.7 (6.4-9.2')		8	Gravel in sand.						
			Moist, (v. firm), tan, CLAY with trace Silt and fine Sand, trace gravel at top (CL) (Native)	FW-WB-39-CS-7.7- 8.3 (7.7-8.3')	Α				
FW-WB-39-CS-7.7-	Gravel in sand.	9	BOB @ 8.3'	(1.1 0.0)					
8.3 (9.2-10')	Moist, (v. firm), tan, CLAY with trace Silt and fine Sand, trace gravel at top (CL) (Native).	10							
	BOB @ 10.0']
		11							
		12							
		13							

NOTES: A = Archive; B = Bioassay; C = Chemistry Analysis included PCB Aroclors, Organochlorine Pesticides, Semivolatile Organics, Metals (RCRA + Cu + Zn), oil and grease, Total Organic Carbon, and Acid Volatile Sulfides - Simultaneuosly Extracted Metals

G = Grain Size; GT = Geotechnical testing including Grain Size, Specific Gravity, Moisture Content/Bulk Density P = PCB Congeners

 $^{\star}\,$ In-situ compaction based on linear compaction ratios.

MS/MSD collected at FW-WB-39-CS-5.3-7.7.

Lots of fluidized sediment in top of core. Probably better recovery than measured.

CORING NOTES: Refusal at 10'.



October 2002

Date: 10/24/02 Time: 1200 System: Cable vibracore

SEDIMENT CORE: WB-40 Northing: 2323420.98 Easting: 2832309.96 Datum: NAD 83 Indiana West Mudline Elev. (ft): 576.5 Station Description: North side of river in outfall stream

Depth to Mudline (ft): 0.9 Penetration (ft): 10.8 Recovery (ft): 9.5 % Recovery: 88

Station Description. Notin side of fiver in outlants	su cam.

	le Depth (ft) Visual Sample Description (In-situ) (ft) Visual Sample Description (Compacted) Sample Dept Visual Sample Description (Compacted) Sample Dept Visual Sample Description (Compacted) V. wet, (v. soft), dark brown to black, clayey SILT with trace fine Sand; strong petroleum odor; high								
Sample No. and Sample Depth (ft)	Visual Sample Description (In-situ)*	-	Visual Sample Description (Compacted)	Sample No. and Sample Depth (ft)	TESTING	Gravel	Sand	Silt	Clay
		1							
				FW-WB-40-CS-0-3	в,с				
FW-WB-40-CS-0-3		2		(0-3')					
(0-3.4')			Coarse sand sized material at 2.2 ft below mudline						
	Coarse sand sized material at 2.5 ft below mudline.	3							
			Wet, (soft), dark olive, clayey SILT with fine to medium Sand (ML).						
	Wet, (soft), dark olive, clayey SILT with fine to medium Sand (ML).	4		FW-WB-40-CS-3- 5.4 (3-5.4')	A				
FW-WB-40-CS-3- 5.4		5	Texture change; softer above; peaty below; sandier at base.	(3-3.4)					
(3.4-6.2')	Texture change; softer above; peaty below; sandier at base.								
	sandier at base.	6	Wet, (soft), dark olive clayey, sandy, SILT (ML); trace shell hash; some trace organics; peaty.	FW-WB-40-CS-5.4- 6.9	С				
FW-WB-40-CS-5.4-	Wet, (soft), dark olive clayey, sandy, SILT (ML);		Snail shells at top of interval.	(5.4-6.9') D1					
6.9 (6.2-7.9')	trace shell hash; some trace organics; peaty. Snail shells at top of interval.	7	Moist to wet, (loose to dense), dark tan, silty, fine						
		8	to medium SAND (SM); laminated; trace to some shell hash (increasing with depth) (Native).	FW-WB-40-CS-6.9- 9.5	A,G				
	Moist to wet, (loose to dense), dark tan, silty, fine to medium SAND (SM); laminated; trace to some		Wood.	(6.9-9.5') D2					
	shell hash (increasing with depth) (Native).	9							
FW-WB-40-CS-6.9- 9.5			BOB @ 9.5'						
(7.9-10.8')	Wood.	10							
	BOB @ 10.8'	11							
		12							
		13							

NOTES: A = Archive; B = Bioassay; C = Chemistry Analysis included PCB Aroclors, Organochlorine Pesticides, Semivolatile Organics, Metals (RCRA + Cu + Zn), oil and grease, Total Organic Carbon, and Acid Volatile Sulfides - Simultaneuosly Extracted Metals

G = Grain Size; GT = Geotechnical testing including Grain Size, Specific Gravity, Moisture Content/Bulk Density P = PCB Congeners

 $^{\star}\,$ In-situ compaction based on linear compaction ratios.

D1 = A duplicate was collected for FW-WB-40-CS-5.4-6.9, FW-WB-56-CS-5.4-6.9, and analyzed for chemistry.

D2 = A duplicate was collected for FW-WB-40-CS-6.9-9.5, FW-WB-62-CS-6.9-9.5, and was analyzed for grain size.

CORING NOTES: Refusal at 10.8'.



October 2002

SEDIMENT CORE: WB-41 Northing: 2323378.3 Depth to Mudline (ft): 1.5 Date: 10/24/02 Easting: 2832301.8 Penetration (ft): 9.4 Time: 1235 Datum: NAD 83 Indiana West Recovery (ft): 8.1 System: Cable vibracore Mudline Elev. (ft): 575.9 % Recovery: 86

Station Description: Center of river south of Calumet Flat outfall.

	DESCRIPT	ION OF	SEDIMENT						
Sample No. and Sample Depth (ft)	Visual Sample Description (In-situ)*	Depth (ft)	Visual Sample Description (Compacted)	Sample No. and Sample Depth (ft)	TESTING	Gravel	Sand	Silt	Clay
FW-WB-41-CS-0- 0.8 (0-0.9')	V. wet, (v. soft to firm), black, clayey, sandy SILT; strong peat odor; sheen; abundant misc. organics throughout; twigs.	1	V. wet, (v. soft to firm), black, clayey, sandy SILT; strong peat odor; sheen; abundant misc. organics throughout; twigs.	FW-WB-41-CS-0- 0.8 (0-0.8')	Α				
	V. wet, (v. soft), black, clayey SILT with fine Sand; strong petroleum odor; sheen; abundant misc. organics increasing with depth; probable coal tar globules present (small).	2	V. wet, (v. soft), black, clayey SILT with fine Sand; strong petroleum odor; sheen; abundant misc. organics increasing with depth; probable coal tar globules present (small).	FW-WB-41-CS-0.8- 4.7 (0.8-4.7')	С				
FW-WB-41-CS-0.8- 4.7 (0.9-5.5')		4							
			Sandy zone with increased fibrous organics (peaty); coal at base of interval.						
	Sandy zone with increased fibrous organics (peaty); coal at base of interval.	5	Wet, (v. soft), olive, clayey, SILT with fine Sand (ML); trace shell hash.	FW-WB-41-CS-4.7-	A,GT				
FW-WB-41-CS-4.7- 6.1 (5.5-7.1')	Wet, (v. soft), olive, clayey, SILT with fine Sand (ML); trace shell hash.	6	Dark band at 5.5 ft below mudline.	(4.7-6.1')					
(0.0 7.1)	Dark band at 6.4 ft below mudline.	7	Wet, (loose), olive to dark tan, silty, fine to medium SAND with Clay (SM) (siltier at top, sandier at base); some shell hash increasing with depth; trac	8.1	в,с				
FW-WB-41-CS-6.1- 8.1	Wet, (loose), olive to dark tan, silty, fine to medium SAND with Clay (SM) (siltier at top, sandier at	8	twigs. (Native)						
(7.1-9.4')	base); some shell hash increasing with depth; trace twigs. (Native)	9	BOB @ 8.1'						
	BOB @ 9.4'	10							
		11							
		12							
		13							

NOTES: A = Archive; B = Bioassay; C = Chemistry Analysis included PCB Aroclors, Organochlorine Pesticides, Semivolatile Organics, Metals (RCRA + Cu + Zn), oil and grease, Total Organic Carbon, and Acid Volatile Sulfides - Simultaneuosly Extracted Metals

G = Grain Size; GT = Geotechnical testing including Grain Size, Specific Gravity, Moisture Content/Bulk Density P = PCB Congeners

CORING NOTES: Refusal at 9.4'.



^{*} In-situ compaction based on linear compaction ratios.

October 2002

SEDIMENT CORE: WB-42 Northing: 2323355.2 Easting: 2832291.0 Date: 10/24/02 Time: 1300 Datum: NAD 83 Indiana West System: Cable vibracore Mudline Elev. (ft): 577.2

Depth to Mudline (ft): 0.2 Penetration (ft): 11.7 Recovery (ft): 10.2 % Recovery: 87

Station Description: South side of river across from Calumet Flexicore. Lab Grain Size (%)

	DESCRIPT	ON OF	SEDIMENT	T	ပ				
Sample No. and Sample Depth (ft)	Visual Sample Description (In-situ)*	Depth (ft)	Visual Sample Description (Compacted)	Sample No. and Sample Depth (ft)	TESTING	Gravel	Sand	Silt	Clay
FW-WB-42-CS-0- 1.5 (0-1.7')	V. wet, (v. soft), black, clayey SILT, with fine to medium Sand; strong petroleum odor; sheen; abundant organics throughout.	1	V. wet, (v. soft), black, clayey SILT, with fine to medium Sand; strong petroleum odor; sheen; abundant organics throughout.	FW-WB-42-CS-0- 1.5 (0-1.5')	A				
	V. wet, (v. soft to soft), clayey SILT with fine to medium Sand; less sand and and misc. organics than above; strong petroleum odor; sheen; some misc. organics.	3	V. wet, (v. soft to soft), clayey SILT with fine to medium Sand; less sand and and misc. organics than above; strong petroleum odor; sheen; some misc. organics.	FW-WB-42-CS-1.5-					
FW-WB-42-CS-1.5- 6 (1.7-6.9')		4		6 (1.5-6')	B,C,GT				
		5 6							
FW-WB-42-CS-6-	Wet, (soft), dark brown to black sandy SILT with Clay; abundant plant material - peaty (OH).	7	Wet, (soft), dark brown to black sandy SILT with Clay; abundant plant material - peaty (OH).	FW-WB-42-CS-6- 7.7 (6-7.7')	A				
7.7 (6.9-8.9')		8	Wet, (soft), dark olive SILT with fine to medium Sand and Clay (ML).	8.6 (7.7-8.6')	С				
FW-WB-42-CS-7.7- 8.6 (8.9-9.9')	Wet, (soft), dark olive SILT with fine to medium Sand and Clay (ML).	9	Wet, loose, dark tan to olive, silty SAND with Clay (SM) (Native)	FW-WB-42-CS-8.6- 10 (8.6-10')	A				
FW-WB-42-CS-8.6- 10 (9.9-11.5')	Wet, loose, dark tan to olive, silty SAND with Clay (SM) (Native)	11	Soft, olive, sandy, clayey SILT with shell hash. BOB @ 10.2'						
	Soft, olive, sandy, clayey SILT with shell hash. BOB @ 11.7'	12							
		13							

NOTES: A = Archive; B = Bioassay; C = Chemistry Analysis included PCB Aroclors, Organochlorine Pesticides, Semivolatile Organics, Metals (RCRA + Cu + Zn), oil and grease, Total Organic Carbon, and Acid Volatile Sulfides - Simultaneuosly Extracted Metals

G = Grain Size; GT = Geotechnical testing including Grain Size, Specific Gravity, Moisture Content/Bulk Density P = PCB Congeners

CORING NOTES: Sheen created from coring.



^{*} In-situ compaction based on linear compaction ratios.

October 2002

Date: 10/16/02 Time: 1600

System: Cable vibracore Station Description:

SEDIMENT CORE: WB-43

Northing: 2319219.8 Easting: 2843900.8 Datum: NAD 83 Indiana West Mudline Elev. (ft): 577.0

Depth to Mudline (ft): 1.2 Penetration (ft): 11.5 Recovery (ft): 9.9 % Recovery: 86

	DESCRIPT	ION OF	SEDIMENT	1	_o		1	ļ	
Sample No. and Sample Depth (ft)	Visual Sample Description (In-situ)*	Depth (ft)	Visual Sample Description (Compacted)	Sample No. and Sample Depth (ft)	TESTING	Gravel	Sand	Silt	ō
FW-WB-43-CS-0-2 (0-2.3')	V. wet, (v. soft), black, clayey, sandy SILT with lenses of organics throughout; extensive petroleum sheen and odor; woody debris on top of core.	1	V. wet, (v. soft), black, clayey, sandy SILT with lenses of organics throughout; extensive petroleum sheen and odor; woody debris on top of core.	FW-WB-43-CS-0-2 (0-2')	B,C,P				
		2							
FW-WB-43-CS-2-5 (2.3-5.8')	V. wet, (v. soft), black to brown, clayey SILT with fine Sand; petroleum sheen and odor decreases with depth, but is still there; human hair observed; clay increasing with depth; sand decreasing with depth.	3	V. wet, (v. soft), black to brown, clayey SILT with fine Sand; petroleum sheen and odor decreases with depth, but is still there; human hair observed; clay increasing with depth; sand decreasing with depth. Zone of coal tar.	FW-WB-43-CS-2-5 (2-5')	A				
	Zone of coal tar.	5	Zone of coal tar.						
	Zone of coal tar.								
FW-WB-43-CS-5-		6		FW-WB-43-CS-5- 7.7 (5-7.7')	A				
7.7 (5.8-8.9')		7	Zone of coal tar type material. Zone of coal tar type material.	(6)					
	Zone of coal tar type material.	8	Peat zone 1-2" Wet, (soft), olive brown, clayey SILT with fine Sand						
	Zone of coal tar type material. Peat zone 1-2"	9	and fine organics (fibers) (OH). (Native?)	FW-WB-43-CS-7.7- 9.9	в,с				
FW-WB-43-CS-7.7-	Wet, (soft), olive brown, clayey SILT with fine Sand and fine organics (fibers) (OH). (Native?)			(7.7-9.9')					
9.9 (8.9-11.5')		10	BOB @ 9.9'						
		11							
	BOB @ 11.5'	12							
		13							

NOTES: A = Archive; B = Bioassay; C = Chemistry Analysis included PCB Aroclors, Organochlorine Pesticides, Semivolatile Organics, Metals (RCRA + Cu + Zn), oil and grease, Total Organic Carbon, and Acid Volatile Sulfides - Simultaneuosly Extracted Metals

G = Grain Size; GT = Geotechnical testing including Grain Size, Specific Gravity, Moisture Content/Bulk Density P = PCB Congeners

CORING NOTES: Petroleum sheen created from coring - petroleum odor.



^{*} In-situ compaction based on linear compaction ratios.

October 2002

Date: 10/16/02 Time: 1635

System: Cable vibracore Station Description:

SEDIMENT CORE: WB-44

Northing: 2319193.8 Easting: 2843879.2 Datum: NAD 83 Indiana West Mudline Elev. (ft): 576.5

Depth to Mudline (ft): 1.7 Penetration (ft): 11 Recovery (ft): 9.2 % Recovery: 84

Lab Grain Size (%)

	DESCRIPT	ION OF	SEDIMENT		(D				ì
Sample No. and Sample Depth (ft)	Visual Sample Description (In-situ)*	Depth (ft)	Visual Sample Description (Compacted)	Sample No. and Sample Depth (ft)	TESTING	Gravel	Sand	Silt	Clav
FW-WB-44-CS-0- 1.2 (0-1.4')	V. wet, (v. soft), black, sandy, clayey SILT with fine organics throughout; petroleum sheen and odor (extensive).	1	V. wet, (v. soft), black, sandy, clayey SILT with fine organics throughout; petroleum sheen and odor (extensive).	FW-WB-44-CS-0- 1.2 (0-1.2')	A			,	
	grading to V. wet, (v. soft), black-brown, clayey SILT with fine Sand and petroleum sheen and odor; more like an oil product.	2	grading to V. wet, (v. soft), black-brown, clayey SILT with fine Sand and petroleum sheen and odor; more like an oil product.						
FW-WB-44-CS-2-4		3		FW-WB-44-CS-2-4 (2-4')	С				Ī
(2.4-4.8')		4							
		5	Peat layer; brown, soft (PT).	FW-WB-44-CS-4.4- 5.6 (4.4-5.6')	A				
FW-WB-44-CS-4.4- 5.6	Peat layer; brown, soft (PT).	6							
(5.3-6.7')		7	Moist, (soft), brown to olive, clayey SILT with fine Sand and high organic content; scattered shell fragments; no obvious sheen (OH). (Native?)	FW-WB-44-CS-6-8	С				
	Moist, (soft), brown to olive, clayey SILT with fine Sand and high organic content; scattered shell fragments; no obvious sheen (OH). (Native)			(6-8')					
FW-WB-44-CS-6-8		8							
(7.2-9.6')		9							
		10	BOB @ 9.2'						Ì
		11							Ì
	BOB @ 11.0'								1
		12							
		13							

NOTES: A = Archive; B = Bioassay; C = Chemistry Analysis included PCB Aroclors, Organochlorine Pesticides, Semivolatile Organics, Metals (RCRA + Cu + Zn), oil and grease, Total Organic Carbon, and Acid Volatile Sulfides - Simultaneuosly Extracted Metals

G = Grain Size; GT = Geotechnical testing including Grain Size, Specific Gravity, Moisture Content/Bulk Density P = PCB Congeners

CORING NOTES: Strong petroleum odor; sheen created from coring.



^{*} In-situ compaction based on linear compaction ratios.

October 2002

SEDIMENT CORE: WB-45 Date: 10/16/02

Time: 1715

System: Cable vibracore Station Description:

Northing: 2319167.7 Easting: 2843865.7 Datum: NAD 83 Indiana West Mudline Elev. (ft): 576.9

Depth to Mudline (ft): 1.2 Penetration (ft): 11.4 Recovery (ft): 10.0 % Recovery: 88

	Pe Depth (ft) Visual Sample Description (in-situ)* V. wet, (v. soft), sandy, clayey SILT with abundant fine organics throughout; petroleum sheen and odor; some peat material; sheen ends at 1 ft below mudline (OH). 3-45-CS-2-3.9-3.4-4*) Tan, fine to medium SAND lense with Silt (SW); organics reduce with depth. Same as 0 to 3.6 ft below mudline. 5 Tan, fine to medium SAND lense with Silt (SW). Same as 0 to 3.6 ft below mudline. 5 Tan, fine to medium SAND lense with Silt (SW). Same as 0 to 3.2 ft below mudline. 5 Tan, fine to medium SAND lense with Silt (SW). Same as 0 to 3.2 ft below mudline. 5 Tan, fine to medium SAND lense with Silt (SW). Same as 0 to 3.2 ft below mudline.				<u>o</u>				l
Sample No. and Sample Depth (ft)	Visual Sample Description (In-situ)*		Visual Sample Description (Compacted)	Sample No. and Sample Depth (ft)	TESTING	Gravel	Sand	Silt	Clav
	fine organics throughout; petroleum sheen and odor; some peat material; sheen ends at 1 ft below		V. wet, (v. soft), sandy, clayey SILT with abundant fine organics throughout; petroleum sheen and odor; some peat material; sheen ends at 1 ft below mudline (OH).	FW-WB-45-CS-0-2 (0-2')	A	,			
		2							
FW-WB-45-CS-2-		3		FW-WB-45-CS-2- 3.9 (2-3.9')	с,дт				
			Tan, fine to medium SAND lense with Silt (SW); organics reduce with depth.	(2-0.0)					
		4	Same as 0 to 3.2 ft below mudline.						
	Same as 0 to 3.6 ft below mudline.	5	Tan, fine to medium SAND lense with Silt (SW).	FW-WB-45-CS-3.9-	С				
	Top fine to medium CAND lenge with City (CAN)	6	Same as 0 to 3.2 ft below mudline.	6.9 (3.9-6.9')					
(4.4-7.9')	Tan, fine to medium SAND lense with Slit (SW).								
	Same as 0 to 3.6 ft below mudline.		Wet to moist, (loose), tan, silty, fine to medium SAND to fine to medium SAND with Silt (SM/SW) (Native).						
	SAND to fine to medium SAND with Silt (SM/SW)			FW-WB-45-CS-6.9- 10 (6.9-10')	A,G				
FW-WB-45-CS-6.9- 10 (7.9-11.4')		9							
		10	BOB @ 10'						
		11							
	BOB @ 11.4'	12							
		13							i

NOTES: A = Archive; B = Bioassay; C = Chemistry Analysis included PCB Aroclors, Organochlorine Pesticides, Semivolatile Organics, Metals (RCRA + Cu + Zn), oil and grease, Total Organic Carbon, and Acid Volatile Sulfides - Simultaneuosly Extracted Metals

G = Grain Size; GT = Geotechnical testing including Grain Size, Specific Gravity, Moisture Content/Bulk Density P = PCB Congeners

CORING NOTES: Petroleum odor and sheen created by coring.



^{*} In-situ compaction based on linear compaction ratios.

October 2002
Northing: 2320500.1

Date: 10/17/02 Time: 1425 System: Cable vibracore

Station Description:

SEDIMENT CORE: WB-46

Easting: 2839349.9 Datum: NAD 83 Indiana West Mudline Elev. (ft): 579.0 Depth to Mudline (ft): 0.9 Penetration (ft): 11 Recovery (ft): 9.7 % Recovery: 88

Lab Grain Size (%

	th (ft)								i
Sample No. and Sample Depth (ft)	Visual Sample Description (In-situ)*		Visual Sample Description (Compacted)	Sample No. and Sample Depth (ft)	TESTING	Gravel	Sand	Silt	
FW-WB-46-CS-0-2 (0-2.3')		1		FW-WB-46-CS-0-2 (0-2')					
		2							
FW-WB-46-CS-2-	fine Sand; scattered shell fragments; peaty		fine Sand; scattered shell fragments; peaty		C,G				
5.2 (2.3-5.9')									
		5	Note: May be compromised by above.						
	Wet, (loose), tan to brown, silty SAND with Clay;	6		FW-WB-46-CS-5.2-	B,C,G				
FW-WB-46-CS-5.2-	scattered shell fragments (SM) (Native).	7		_	5,0,0				ĺ
8 (5.9-9')									1
		8		EW WD 46 CS 9					
		9		9.7	A				
FW-WB-46-CS-8- 9.7 (9-11')	on (ov) (naivo).	10	DOD @ 0.7!						
(9-11)		11	BOB @ 9.7'						1
	BOB @ 11.0'	11							
		12							Ī
		13							1

NOTES: A = Archive; B = Bioassay; C = Chemistry Analysis included PCB Aroclors, Organochlorine Pesticides, Semivolatile Organics, Metals (RCRA + Cu + Zn), oil and grease, Total Organic Carbon, and Acid Volatile Sulfides - Simultaneuosly Extracted Metals

G = Grain Size; GT = Geotechnical testing including Grain Size, Specific Gravity, Moisture Content/Bulk Density P = PCB Congeners

CORING NOTES: Petroleum sheen created during coring.



^{*} In-situ compaction based on linear compaction ratios.

October 2002

Northing: 2320460.4

Date: 10/17/02 Time: 1540 System: Cable vibracore

SEDIMENT CORE: WB-47

Station Description: Center of river.

Easting: 2839321.7 Datum: NAD 83 Indiana West Mudline Elev. (ft): 579.3

Depth to Mudline (ft): 0.6 Penetration (ft): 11.4 Recovery (ft): 10 % Recovery: 88

	DESCRIPT	ION OF	SEDIMENT		.,				
Sample No. and Sample Depth (ft)	Visual Sample Description (In-situ)*	Depth (ft)	Visual Sample Description (Compacted)	Sample No. and Sample Depth (ft)	TESTING	Gravel	Sand	Silt	Clay
FW-WB-47-CS-0- 2.4 D	V. wet, (v. loose), black, silty fine to medium SAND with abundant petroleum sheen and odor; woody debris; hair; misc. organics.	1	V. wet, (v. loose), black, silty fine to medium SAND with abundant petroleum sheen and odor; woody debris; hair; misc. organics.	FW-WB-47-CS-0- 2.4 D (0-2.4')	C,G				
(0-2.8')		2							
	grading to V. wet, (v. soft to soft), black, sandy, clayey SILT with moderate to abundant petroleum sheen and odor and organics.	3	grading to V. wet, (v. soft to soft), black, sandy, clayey SILT with moderate to abundant petroleum sheen and odor and organics.	FW WP 47 CC 2.4					
FW-WB-47-CS-2.4- 5.6 (2.8-6.4')	Tan, fine SAND lense (1").	4	Tan, fine SAND lense (1").	FW-WB-47-CS-2.4- 5.6 (2.4-5.6')	A				
		5 6							
	Wet to moist, (soft), olive brown to black grading to brown, clayey SILT with fine Sand and scattered organics and shell frags (ML); clay increases with depth. (Native?) Tan, fine SAND lense (1-2") at 7.1 ft below	7	Tan, fine SAND lense (1-2") at 6.2 ft below mudline. Wet to moist, (soft), olive brown to black grading to brown, clayey SILT with fine Sand and scattered organics and shell frags (ML); clay increases with depth. (Native?)	FW-WB-47-CS-5.6- 8 MS/MSD (5.6-8')	C,G				
8 MS/MSD (6.4-9.2')	mudline.	9		FW-WB-47-CS-8- 10 (8-10')	A				
FW-WB-47-CS-8- 10 (9.2-11.4')		10							
(0.2-11.4)		11	BOB @ 10.0'						
	BOB @ 11.4'	12							
		13							Ī

NOTES: A = Archive; B = Bioassay; C = Chemistry Analysis included PCB Aroclors, Organochlorine Pesticides, Semivolatile Organics, Metals (RCRA + Cu + Zn), oil and grease, Total Organic Carbon, and Acid Volatile Sulfides - Simultaneuosly Extracted Metals

G = Grain Size; GT = Geotechnical testing including Grain Size, Specific Gravity, Moisture Content/Bulk Density P = PCB Congeners

* In-situ compaction based on linear compaction ratios.

FW-WB-53-CS-0-2.4 is the duplicate of FW-WB-47-CS-0-2.4 and was analyzed for chemistry.

MS/MSD was collected at FW-WB-47-CS-5.6-8.



October 2002

SEDIMENT CORE: WB-48 Date: 10/17/02 Time: 1600

System: Cable vibracore Station Description:

Northing: 2320420.3 Easting: 2839284.48 Datum: NAD 83 Indiana West Mudline Elev. (ft): 579.1

Depth to Mudline (ft): 0.8 Penetration (ft): 11.1 Recovery (ft): 9.6 % Recovery: 87

	DESCRIPT	ION OF	SEDIMENT	1	ဗ				l
Sample No. and Sample Depth (ft)	Visual Sample Description (In-situ)*	Depth (ft)	Visual Sample Description (Compacted)	Sample No. and Sample Depth (ft)	TESTING	Gravel	Sand	Silt	Clay
FW-WB-48-CS-0- 1.8 (0-2.1')	V. wet, (v. soft), black, organic, clayey SILT with Sand and abundant wood/organics; petroleum sheen and odor; 3" wood piece on top. #	1	V. wet, (v. soft), black, organic, clayey SILT with Sand and abundant wood/organics; petroleum sheen and odor; 3" wood piece on top. #	FW-WB-48-CS-0- 1.8 (0-1.8')	A				
(0-2.1)	Wet, (loose), tan to gray, silty, fine to medium SAND with organics; lense of petroleum here.	2	Wet, (loose), tan to gray, silty, fine to medium SAND with organics; lense of petroleum here.	(0-1.6)					
FW-WB-48-CS-1.8- 4 (2.1-4.6')	Wet to moist, (soft), olive brown, clayey SILT with fine Sand; scattered organics and shell fragments (ML).	3	Wet to moist, (soft), olive brown, clayey SILT with fine Sand; scattered organics and shell fragments (ML) (Native?) Clay increasing with depth.	FW-WB-48-CS-1.8- 4 (1.8-4')	B,C,P				
	Clay increasing with depth.	4							
FW-WB-48-CS-4-6	Wet to moist, (soft), olive brown, clayey SILT with fine Sand; scattered organics and shell fragments (ML) (Native?).	5		FW-WB-48-CS-4-6 (4-6')	C,G				
(4.6-7')	Clay increasing with depth.	7		FW-WB-48-CS-6-8 (6-8')	A				
FW-WB-48-CS-6-8 (7-9.3')		8		FW-WB-48-CS-8-					<u> </u>
(1 6.6)		9		9.6 (8-9.6')	A				
FW-WB-48-CS-8- 9.6 (9.3-11.1')		10	BOB @ 9.6'						
		11							
	BOB @ 11.1'	12							
		13							

NOTES: A = Archive; B = Bioassay; C = Chemistry Analysis included PCB Aroclors, Organochlorine Pesticides, Semivolatile Organics, Metals (RCRA + Cu + Zn), oil and grease, Total Organic Carbon, and Acid Volatile Sulfides - Simultaneuosly Extracted Metals

- G = Grain Size; GT = Geotechnical testing including Grain Size, Specific Gravity, Moisture Content/Bulk Density P = PCB Congeners
- * In-situ compaction based on linear compaction ratios.
- # Significant amount of hair, woody debris and petroleum (top 1.1 ').



October 2002

Date: 10/23/02 Time: 1600 System: Cable vibracore

FW-WB-49-CS-7.1

7.9

(7.1-7.9) FW-WB-49-CS-7.9-

(7.9-8.6')

SEDIMENT CORE: WB-49

Station Description: North side of river

Northing: 2323449.6 Easting: 2831962.3 Datum: NAD 83 Indiana West Mudline Elev. (ft): 577.1

Depth to Mudline (ft): 0.3 Penetration (ft): 11.1 Recovery (ft): 8.6 % Recovery: 77

Lab Grain Size (%)

DESCRIPTION OF SEDIMENT FESTING Sample No. and Depth Sample No. and Visual Sample Description (In-situ)* **Visual Sample Description (Compacted)** Sample Depth (ft) Sample Depth (ft) (ft) Silt FW-WB-49-CS-0-1 V. wet, (v. soft to form), black to green, clayey, V. wet, (v. soft to form), black to green, clayey, FW-WB-49-CS-0-1 Α sandy SILT; strong petroleum odor and sheen; sandy SILT; strong petroleum odor and sheen; abundant misc. organics. (0-1.3')Hard abundant misc. organics. (0-1')gravelly at interface. gravelly at interface. FW-WB-49-CS-1-V. wet, (soft to v. soft), gray clayey SILT; laminated FW-WB-49-CS-1-Α 1.6 black layers. Hard, gravelly at interface. 1.6 (1.3-2.1')V. wet, (soft to v. soft), gray clayey SILT; laminated (1-1.6') black layers. Hard, gravelly at interface. V. wet, (soft to v. soft), black, clayey SILT with fine to medium Sand (ML) V. wet, (soft to v. soft), black, clayey SILT with fine FW-WB-49-CS-1.6-B,C,GT to medium Sand (ML). 3 (1.6-4.5')Р FW-WB-49-CS-1.6-4.5 Increase in misc. organics - peaty from 3.4 to 4.5 ft (2.1-5.8') below mudline. Wet, (soft), olive to dark olive, clayey SILT with fine Increase in misc. organics - peaty from 4.4 to 5.8 fl 5 Sand (ML); trace shell hash throughout. below mudline. FW-WB-49-CS-4.5-С 6 Wet, (soft), olive to dark olive, clayey SILT with Darker, higher organics from 6.2 to 6.7 ft below (4.5-7.1') (MS/MSD) fine Sand (ML); trace shell hash throughout. mudline Higher clay content, no shells from 6.7 to 7.1 ft 7 FW-WB-49-CS-4.5-FW-WB-49-CS-7.1 Wet, (loose), dark tan to white, clayey, silty fine to Α 7.1 7.9 medium SAND with trace Gravel (SM); shell hash (5.8-9.2')(7.1-7.9') throughout. (Native) 8 Darker, higher organics from 8 to 8.6 ft below Moist, (firm), tan, silty CLAY (CL) (clean) (Native). FW-WB-49-CS-7.9-Α mudline. 8.6 Higher clay content, no shells from 8.6 to 9.2 ft (7.9-8.6')BOB @ 8.6' 9 below mudline.

NOTES: A = Archive; B = Bioassay; C = Chemistry Analysis included PCB Aroclors, Organochlorine Pesticides, Semivolatile Organics, Metals (RCRA + Cu + Zn), oil and grease, Total Organic Carbon, and Acid Volatile Sulfides - Simultaneuosly Extracted Metals

G = Grain Size; GT = Geotechnical testing including Grain Size, Specific Gravity, Moisture Content/Bulk DensityP = PCB Congeners

10

11

12

13

* In-situ compaction based on linear compaction ratios.

Wet, (loose), dark tan to white, clayey, silty fine to

medium SAND with trace Gravel (SM); shell hash

Moist, (firm), tan, silty CLAY (CL) (clean) (Native).

BOB @ 11.1'

throughout. (Native)

MS/MSD collected at FW-WB-49-CS-4.5-7.1.

CORING NOTES: Hard layer encountered at 1.5' below mudline.



October 2002

Time: 1640 System: Cable vibracore

Date: 10/24/02

SEDIMENT CORE: WB-49geo

Northing: 2323449.6 Easting: 2831962.3 Datum: NAD 83 Indiana West Mudline Elev. (ft): 577.1 Station Description: North side of river.

Depth to Mudline (ft): 0.3 Penetration (ft): 11 Recovery (ft): 9.1 % Recovery: 83

Lab Grain Size (%)

	DESCRIPT	ON OF	SEDIMENT		g				l
Sample No. and Sample Depth (ft)	Visual Sample Description (In-situ)*	Depth (ft)	Visual Sample Description (Compacted)	Sample No. and Sample Depth (ft)	TESTING	Gravel	Sand	Silt	Clay
		1 2							
		3	V. wet, (soft to v. soft), black, clayey SILT with fine		UU,CO				
	V. wet, (soft to v. soft), black, clayey SILT with fine Sand.	4	Sand.	WB-49 2.8-4.5 (2.8-4.5')	00,00				
WB-49 2.8-4.5 (3.4-5.4')		5	Headspace ranged from 0.01' to 0.015'.						
	Headspace ranged from 0.01' to 0.015'.	6	Wet, (soft), olive to dark olive, clayey SILT with fine Sand; trace shell hash (ML).	WB-49 5.2-7.0 (5.2-7.0')	ии,со				
	Wet, (soft), olive to dark olive, clayey SILT with fine Sand (ML); trace shell hash.	7	Wet, (Soft), dark brown, clayey SILT with fine to medium Sand (ML). Headspace ranged from 0.0' to 0.003'.						
	Wet, (Soft), dark brown, clayey SILT with fine to medium Sand (ML). Headspace ranged from 0.0' to 0.003'.	8	Wet, (loose), dark tan to white, clayey, silty fine to medium SAND with trace Gravel (SM); shell hash throughout.	WB-49 7.0-8.0 (7.0-8.0')	A				
WB-49 8.5-9.7	Wet, (loose), dark tan to white, clayey, silty fine to medium SAND with trace Gravel (SM); shell hash throughout.	10	BOB @ 9.1'						
	BOB @ 9.1'	11							
		12							

NOTES: A = Archive; **UU** = UU Triaxial Shear Testing; **CO** = Consolidation Testing

Headspace measurements taken in tenths of a foot from the top of the sediment to the top of the aluminum pipe.



^{*} In-situ compaction based on linear compaction ratios.

October 2002

Date: 10/23/02 Time: 1520

System: Cable vibracore Station Description: Center of river.

SEDIMENT CORE: WB-50

Northing: 2323423.9 Easting: 2831967.4 Datum: NAD 83 Indiana West Mudline Elev. (ft): 576.0

Depth to Mudline (ft): 1.4 Penetration (ft): 8.7 Recovery (ft): 7.8 % Recovery: 90

Lab Grain Size (%)

	DESCRIPT	ION OF	SEDIMENT	T	ဖ				l
Sample No. and Sample Depth (ft)	Visual Sample Description (In-situ)*	Depth (ft)	Visual Sample Description (Compacted)	Sample No. and Sample Depth (ft)	TESTING	Gravel	Sand	Silt	Yel
FW-WB-50-CS-0- 0.9 (0-1')	V. wet, (v. soft), black, clayey SILT with fine Sand; abundant misc. organics. Oil at 0.4 ft below mudline; Hard dark brown to olive bentonite plug(?) at 0.9 ft below mudline.	1	V. wet, (v. soft), black, clayey SILT with fine Sand; abundant misc. organics. Oil at 0.4 ft below mudline; Hard dark brown to olive bentonite plug(?) at 0.9 ft below mudline.	FW-WB-50-CS-0- 0.9 (0-0.9')	A				
FW-WB-50-CS-0.9- 2.3 (1-2.6')	V. wet, (v. soft to hard), light gray to black laminated, clayey SILT; fly ash (?) Hard layer, black, laminated, 0.05" to 0.3" thick from 1.3' to 1.5' and 2.1' below mudline.	2	V. wet, (v. soft to hard), light gray to black laminated, clayey SILT; fly ash (?) Hard layer, black, laminated, 0.05" to 0.3" thick from 1.2' to 1.3' and 1.9' below mudline.	FW-WB-50-CS-0.9- 2.3 (0.9-2.3')	С				
FW-WB-50-CS-2.3- 5 (2.6-5.6')	V. wet, (v. soft to soft), dark olive brown to black, clayey SILT with fine to medium Sand; petroleum odor and sheen; abundant misc. organics. 2.6-4.5' silty less sand and fibrous organics.	3	V. wet, (v. soft to soft), dark olive brown to black, clayey SILT with fine to medium Sand; petroleum odor and sheen; abundant misc. organics. 2.3-4' silty less sand and fibrous organics. 4-5' more sand; abundant fibrous organics.	FW-WB-50-CS-2.3- 5 (2.3-5')	A				
	4.5-5.6' more sand; abundant fibrous organics.	5	Wet, (soft), dark olive, clayey SILT with fine to medium Sand (ML/OH); some organics; peaty.						
FW-WB-50-CS-5- 7.8 D (5.6-8.7')	Wet, (soft), dark olive, clayey SILT with fine to medium Sand (ML/OH); some organics; peaty. Peat at 6.4 ft below mudline. SLAG at 7.2 ft below mudline. Clean silt from 7.2-8 ft below mudline.	7	Peat at 5.7 ft below mudline. SLAG at 6.4 ft below mudline. Clean silt from 6.4-7.1 ft below mudline. More fine to medium Sand and increased shell hash at 7.1 ft below mudline. Wet, (loose), silty SAND with trace Clay (SM);	FW-WB-50-CS-5- 7.8 D (5-7.8')	GT				
	More fine to medium Sand and increased shell hash at 8 ft below mudline. Wet, (loose), silty SAND with trace Clay (SM); abundant shell hash in catcher (Native?).	9	abundant shell hash in catcher (Native?). BOB @ 7.8'						
	BOB @ 8.7'	10							
		11							
		12							

NOTES: A = Archive; B = Bioassay; C = Chemistry Analysis included PCB Aroclors, Organochlorine Pesticides, Semivolatile Organics, Metals (RCRA + Cu + Zn), oil and grease, Total Organic Carbon, and Acid Volatile Sulfides - Simultaneuosly Extracted Metals

G = Grain Size; GT = Geotechnical testing including Grain Size, Specific Gravity, Moisture Content/Bulk Density P = PCB Congeners

 $^{\star}\,$ In-situ compaction based on linear compaction ratios.

FW-WB-55-CS-5-7.8 is the duplicate of FW-WB-50-CS-5-7.8 and was analyzed for chemistry.

CORING NOTES: Hard layer encountered at approximately 3 ft below mudline during coring.

Refusal at 8.7'.



October 2002

SEDIMENT CORE: WB-51 Date: 10/23/02

System: Cable vibracore

Northing: 2323408.5 Easting: 2831971.7 Time: 1115

Penetration (ft): 11 Datum: NAD 83 Indiana West Recovery (ft): 8.1 Mudline Elev. (ft): % Recovery: 74

Station Description: South side of river at State Line.

Depth to Mudline (ft): 0.0

	DESCRIPT	SEDIMENT	T						
Sample No. and Sample Depth (ft)	Visual Sample Description (In-situ)*	Depth (ft)	Visual Sample Description (Compacted)	Sample No. and Sample Depth (ft)	TESTING	Gravel	Sand	Silt	
FW-WB-51-CS-0- 1.3 (0-1.8')	V. wet, (soft), brown to black PEAT; stained below 0.2'; moderate to heavy sheen; moderate petroleum odor.	1	V. wet, (soft), brown to black PEAT; stained below 0.2'; moderate to heavy sheen; moderate petroleum odor.	FW-WB-51-CS-0- 1.3 (0-1.3')	A				
FW-WB-51-CS-1.3- 6 (1.8-8.4')	V. wet, (v. soft), black, clayey SILT with fine to medium Sand; heavy sheen; abundant organics; Sandy zone from 2.9 to 3.6 ft below mudline; oily zone from 3.1 to 3.4 ft below mudline.	3	V. wet, (v. soft), black, clayey SILT with fine to medium Sand; heavy sheen; abundant organics; Sandy zone from 2.1 to 2.6 ft below mudline; oily zone from 2.2 to 2.4 ft below mudline. Fine, clayey SILT - clean.	FW-WB-51-CS-1.3- 6 (1.3-6')	в,с				
	Fine, clayey SILT - clean.	4	Oily from 3.2 to 5 ft below mudline.						
	Same as 1.8 to 3.6 ft below mudline.	5	Same as 1.3 to 2.6 ft below mudline.						
	Oily from 4.5 to 7 ft below mudline.	7	Firmer at base; less oil sheen. Wet, (soft), dark brown to olive, clayey, sandy, SILT (ML); sand lense at 6.1 ft below mudline. Peaty zone from 6.3 to 6.7 ft below mudline.	FW-WB-51-CS-6- 8.1 (6-8.1')	B,C,G				
		8	Increased peaty material at base.						
FW-WB-51-CS-6- 8.1 (8.4-11')	Firmer at base; less oil sheen. Wet, (soft), dark brown to olive, clayey, sandy, SILT (ML); sand lense at 8.5 ft below mudline. Peaty zone from 8.8 to 9.4 ft below mudline.	9	BOB @ 8.1'						
	Increased peaty material at base. BOB @ 11.0'	11							
		13							

NOTES: A = Archive; B = Bioassay; C = Chemistry Analysis included PCB Aroclors, Organochlorine Pesticides, Semivolatile Organics, Metals (RCRA + Cu + Zn), oil and grease, Total Organic Carbon, and Acid Volatile Sulfides - Simultaneuosly Extracted Metals

G = Grain Size; GT = Geotechnical testing including Grain Size, Specific Gravity, Moisture Content/Bulk Density P = PCB Congeners

CORING NOTES: Core located on Illinois/Indiana state line.



^{*} In-situ compaction based on linear compaction ratios.